

R71PI3470403MK

aka 71PI3470403MK

Capacitor, film, 0.47 uF, +/-10% Tol, -40/+110C, Power Factor Correction, 275VAC, Lead Spacing=15 mm



Dimensions (mm)

Specifications

| ID | Dimension | Tolerance | Manufacturer: | KEMET |
|----|-----------|-----------|-----------------------------|--------------------------|
| L | 18 | +0.5 | Brand: | Arcotronics |
| H | 16 | +0.1 | Capacitance: | 0.47 uF |
| T | 10 | +0.2 | Temperature Range: | -40/+110C |
| S | 15 | +/-0.4 | Rated Temperature: | 105C |
| LL | 30 | +5 | Voltage @ rated temp: | 630V |
| F | 0.8 | +/-0.05 | Voltage AC: | 275VAC |
| | | | Tolerance: | +/-10% |
| | | | Body Type: | Radial Box |
| | | | Construction: | Wound |
| | | | Application: | Power Factor Correction |
| | | | Dielectric: | Metallized Polypropylene |
| | | | Dissipation Factor @ 1 kHz: | 0.1% |
| | | | Insulation Resistance: | 63.83 GOhm |
| | | | Inductance: | 10 nH |
| | | | Maximum dVdT: | 250v/us |
| | | | Maximum K0: | 315000V^2/us |
| | | | Package Kind: | Bulk |
| | | | Package Type: | Bag |
| | | | Package Quantity: | 500 |