


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [75640-5005](#)
Status: **Active**
Overview: [SFP Stacked Connectors](#)
Description: Small Form-factor Pluggable (SFP) Stacked 2-by-1 Multi-Port Connector with 4 Lightpipes, with Press-fit PC Tails, 45 Degree Mount, 40 Circuits

Documents:

| | |
|--|--|
| 3D Model | Application Specification AS-76090-001 (PDF) |
| Drawing (PDF) | Packaging Specification PK-75462-001 (PDF) |
| Product Specification PS-75310-001 (PDF) | RoHS Certificate of Compliance (PDF) |
| Application Specification AS-75310-001 (PDF) | |



Agency Certification

| | |
|-----|---------|
| CSA | LR19980 |
| UL | E29179 |

General

| | |
|----------------|--|
| Product Family | I/O Connectors |
| Series | 75640 |
| Application | Module-to-Board |
| Component Type | Receptacle |
| Overview | SFP Stacked Connectors |
| Product Name | SFP |
| Type | N/A |
| UPC | 822350905725 |

Physical

| | |
|--------------------------------|---|
| Boot Color | N/A |
| Circuits (Loaded) | 40 |
| Circuits (maximum) | 40 |
| Circuits Detail | 40 |
| Color - Resin | Black, Clear (Blue Tint) |
| Durability (mating cycles max) | 100 |
| Flammability | 94V-0 |
| Gender | Female |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Metal | High Performance Alloy (HPA) |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | High Temperature Thermoplastic, Polycarbonate |
| Net Weight | 25.966/g |
| Number of Rows | 2 |
| Orientation | Right Angle |
| PC Tail Length | 2.07mm |
| PCB Locator | Yes |
| PCB Retention | Yes |
| PCB Thickness - Recommended | 1.60mm |
| Packaging Type | Tray |
| Panel Mount | No |
| Pitch - Mating Interface | 0.80mm |
| Pitch - Termination Interface | 0.80mm |
| Plating min - Mating | 0.762µm |
| Plating min - Termination | 0.762µm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | Yes |

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[75640Series](#)

Use With

[759510999 SFP Dust Plug](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

| Description | Product # |
|------------------------|-----------------------------|
| Extraction Tool, 2 x 1 | 10622029930 |
| Medium | |
| Insertion Tool | 0622030140 |

| | |
|--------------------------------|------------------------------|
| Ports | 2 |
| Surface Mount Compatible (SMC) | Yes |
| Temperature Range - Operating | -40°C to +85°C |
| Termination Interface: Style | Through Hole - Compliant Pin |
| Waterproof / Dustproof | No |

Electrical

| | |
|-------------------------------|------------------|
| Current - Maximum per Contact | 0.5A |
| Grounding to Panel | None |
| Shield Type | EMI Gasket |
| Shielded | Yes |
| Voltage - Maximum | 120V AC (RMS)/DC |

Material Info

Reference - Drawing Numbers

| | |
|---------------------------|----------------------------|
| Application Specification | AS-75310-001, AS-76090-001 |
| Packaging Specification | PK-75462-001 |
| Product Specification | PS-75310-001 |
| Sales Drawing | SD-75640-003 |

This document was generated on 11/27/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION