

R75GD2680AA40J

aka 75GD2680AA40J

Capacitor, film, 0.068 uF, +/-5% Tol, -55/+105C, General Purpose, 160V@85C, Lead Spacing=7.5 mm



Dimensions (mm)

Specifications

| ID | Dimension | Tolerance | Manufacturer: | KEMET |
|----|-----------|-----------|------------------------------|-----------------|
| L | 10 | +0.2 | Capacitance: | 0.068 uF |
| H | 9 | +0.1 | Temperature Range: | -55/+105C |
| T | 4 | +0.1 | Rated Temperature: | 85C |
| S | 7.5 | +/-0.4 | Voltage @ rated temp: | 160V |
| LL | 4 | +2 | Voltage AC: | 90VAC |
| F | 0.5 | +/-0.05 | Tolerance: | +/-5% |
| | | | Body Type: | Radial Box |
| | | | Construction: | Wound |
| | | | Application: | General Purpose |
| | | | Sub Application: | Pulse |
| | | | Dissipation Factor @ 1 kHz: | 0.04% |
| | | | Dissipation Factor @ 10 kHz: | 0.06% |
| | | | Dissipation Factor @ 100kHz: | 0.25% |
| | | | Insulation Resistance: | 100 GOhm |
| | | | Inductance: | 8 nH |
| | | | Maximum dVdT: | 300v/us |
| | | | Maximum K0: | 74000V^2/us |
| | | | Package Kind: | Bulk |
| | | | Package Type: | Bag |
| | | | Package Quantity: | 2000 |