

R75GD3120DQB0K

aka 75GD3120DQB0K

Capacitor, film, 0.12 uF, +/-10% Tol, -55/+105C, General Purpose, 160V@85C, Lead Spacing=7.5 mm



Dimensions (mm)

Specifications

| ID | Dimension | Tolerance | Manufacturer: | KEMET |
|----|-----------|-----------|------------------------------|-----------------|
| L | 10 | +0.2 | Capacitance: | 0.12 uF |
| H | 10.5 | +0.1 | Temperature Range: | -55/+105C |
| T | 5 | +0.1 | Rated Temperature: | 85C |
| S | 7.5 | +/-0.4 | Voltage @ rated temp: | 160V |
| LL | 18.5 | nom | Voltage AC: | 70VAC |
| F | 0.5 | +/-0.05 | Tolerance: | +/-10% |
| | | | Body Type: | Radial Box |
| | | | Construction: | Wound |
| | | | Application: | General Purpose |
| | | | Sub Application: | Pulse |
| | | | Dissipation Factor @ 1 kHz: | 0.05% |
| | | | Dissipation Factor @ 10 kHz: | 0.08% |
| | | | Insulation Resistance: | 100 GOhm |
| | | | Inductance: | 8 nH |
| | | | Maximum dVdT: | 100v/us |
| | | | Maximum K0: | 32000V^2/us |
| | | | Package Kind: | Ammo |
| | | | Package Quantity: | 1600 |