

R75PD2220AAA0J

aka 75PD2220AAA0J

Capacitor, film, 0.022 uF, +/-5% Tol, -55/+105C, General Purpose, 630V@85C, Lead Spacing=7.5 mm



Dimensions (mm)

| ID | Dimension | Tolerance |
|----|-----------|-----------|
| L | 10.5 | +0.2 |
| H | 12 | +0.1 |
| T | 6 | +0.1 |
| S | 7.5 | +/-0.4 |
| LL | 4 | +2 |
| F | 0.5 | +/-0.05 |

Specifications

| | |
|------------------------------|-----------------|
| Manufacturer: | KEMET |
| Capacitance: | 0.022 uF |
| Temperature Range: | -55/+105C |
| Rated Temperature: | 85C |
| Voltage @ rated temp: | 630V |
| Voltage AC: | 220VAC |
| Tolerance: | +/-5% |
| Body Type: | Radial Box |
| Construction: | Wound |
| Application: | General Purpose |
| Sub Application: | Pulse |
| Dissipation Factor @ 1 kHz: | 0.04% |
| Dissipation Factor @ 10 kHz: | 0.06% |
| Dissipation Factor @ 100kHz: | 0.25% |
| Insulation Resistance: | 100 GOhm |
| Inductance: | 8 nH |
| Maximum dVdT: | 600v/us |
| Maximum K0: | 760000V^2/us |
| Package Kind: | Bulk |
| Package Type: | Bag |
| Package Quantity: | 1000 |