

# R76PD1220SE00H

aka 76PD1220SE00H

Capacitor, film, 2200 pF, +/-2.5% Tol, -55/+105C, General Purpose, 630V@85C, Lead Spacing=7.5 mm



## Dimensions (mm)

## Specifications

| ID | Dimension | Tolerance | Manufacturer:                | KEMET             |
|----|-----------|-----------|------------------------------|-------------------|
| L  | 10        | +0.2      | Brand:                       | Arcotronics       |
| H  | 8         | +0.1      | Capacitance:                 | 2200 pF           |
| T  | 3         | +0.1      | Temperature Range:           | -55/+105C         |
| S  | 7.5       | +/-0.4    | Rated Temperature:           | 85C               |
| LL | 4         | +2        | Voltage @ rated temp:        | 630V              |
| F  | 0.5       | +/-0.05   | Voltage AC:                  | 250VAC            |
|    |           |           | Tolerance:                   | +/-2.5%           |
|    |           |           | Body Type:                   | Radial Box        |
|    |           |           | Construction:                | Double Metallized |
|    |           |           | Application:                 | General Purpose   |
|    |           |           | Sub Application:             | Pulse             |
|    |           |           | Dissipation Factor @ 1 kHz:  | 0.03%             |
|    |           |           | Dissipation Factor @ 10 kHz: | 0.04%             |
|    |           |           | Dissipation Factor @ 100kHz: | 0.15%             |
|    |           |           | Insulation Resistance:       | 100 GOhm          |
|    |           |           | Inductance:                  | 8 nH              |
|    |           |           | Maximum dVdT:                | 2800v/us          |
|    |           |           | Maximum K0:                  | 3530000V^2/us     |
|    |           |           | Package Kind:                | Bulk              |
|    |           |           | Package Type:                | Bag               |
|    |           |           | Package Quantity:            | 1500              |