

# R76TN2220SE30K

aka 76TN2220SE30K

Capacitor, film, 0.022 uF, +/-10% Tol, -55/+105C, General Purpose, 1600V@85C, Lead Spacing=22.5 mm



## Dimensions (mm)

ID	Dimension	Tolerance
L	26.5	+0.3
H	15	+0.1
T	6	+0.2
S	22.5	+/-0.4
LL	4	+2
F	0.8	+/-0.05

## Specifications

<b>Manufacturer:</b>	KEMET
<b>Brand:</b>	Arcotronics
<b>Capacitance:</b>	0.022 uF
<b>Temperature Range:</b>	-55/+105C
<b>Rated Temperature:</b>	85C
<b>Voltage @ rated temp:</b>	1600V
<b>Voltage AC:</b>	650VAC
<b>Tolerance:</b>	+/-10%
<b>Body Type:</b>	Radial Box
<b>Construction:</b>	Double Metallized
<b>Application:</b>	General Purpose
<b>Sub Application:</b>	Pulse
<b>Dissipation Factor @ 1 kHz:</b>	0.03%
<b>Dissipation Factor @ 10 kHz:</b>	0.04%
<b>Dissipation Factor @ 100kHz:</b>	0.15%
<b>Insulation Resistance:</b>	100 GOhm
<b>Inductance:</b>	18 nH
<b>Maximum dVdT:</b>	3000v/us
<b>Maximum K0:</b>	9600000V^2/us
<b>Package Kind:</b>	Bulk
<b>Package Type:</b>	Bag
<b>Package Quantity:</b>	805