

Data Sheet | Item Number: 770-101

Locking lever; for flying leads; for manual operation; black

<https://www.wago.com/770-101>



Color: ■ black

Locking system WINSTA® MIDI

Implement your installation project with ease: The locking system from the WINSTA® MIDI product line is the solution for error-free electrical installation. A comprehensive range of accessories rounds out the WINSTA® product line from WAGO. The WINSTA® MIDI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology facilitates exemplary electrification. Due to the built-in test slot, it is possible to check connections even when they are plugged in. This saves time, labor, and money.

WINSTA® MIDI solutions for your electrical installation – protected against mismatching and maintenance-free

The WINSTA® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and consequently more efficient, even more reliable, and error-free. Using this pre-assembled system decreases time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismatching from WAGO makes the electrical installation of electrical components visibly easier.

- pre-assembled versions
- fast, secure installation

Connection data

Connection 1

| | |
|----------------|-----------------------|
| Actuation type | Finger-operated lever |
|----------------|-----------------------|

Mechanical data

| | |
|----------|-------------------------------------|
| Suitable | for flying leads; manually operated |
|----------|-------------------------------------|

Material data

Note (material data)

[Information on material specifications can be found here](#)

| | |
|------------------------------------|------------------|
| Color | black |
| Insulation material (main housing) | Polyamide (PA66) |
| Flammability class per UL94 | V0 |
| Fire load | 0.022 MJ |
| Weight | 0.6 g |

Environmental requirements

| | |
|--|--|
| Processing temperature | -5 ... +40 °C |
| Continuous operating temperature | -35 ... +85 °C |
| Note on continuous operating temperature | Insulating parts for temperatures ≤ 105 °C |

Commercial data

| | |
|-----------------------|---------------|
| Product Group | 20 (Winsta) |
| eCl@ss 10.0 | 27-44-06-92 |
| eCl@ss 9.0 | 27-44-06-92 |
| ETIM 9.0 | EC002863 |
| ETIM 8.0 | EC002863 |
| PU (SPU) | 100 (25) pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4017332660907 |
| Customs tariff number | 85389099990 |

Environmental Product Compliance

| | |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Approvals / Certificates

General approvals



| Approval | Standard | Certificate Name |
|--|----------|------------------|
| VDE VDE Prüf- und Zertifizierungsinstitut | EN 61535 | 40029808 |

Downloads

Environmental Product Compliance

Compliance Search




| | |
|--|-------------------|
| Environmental Product Compliance 770-101 | ↓ |
|--|-------------------|

Documentation

Bid Text


| | | | |
|---------|------------|-----------------|-------------------|
| 770-101 | 19.02.2019 | xml 2.62 KB | ↓ |
| 770-101 | 11.03.2015 | doc 21.50 KB | ↓ |

CAD/CAE-Data

| CAD data | CAE data |
|--|--|
| 2D/3D Models 770-101  | WSCAD Universe 770-101  |
| | ZUKEN Portal 770-101  |

Installation Notes

Locking system



Locking lever, manually operated:

- Push on locking lever
- Pull the connectors apart