

# R777N2100AA00K

aka 777N2100AA00K

Capacitor, film, 0.01 uF, +/-10% Tol, -55/+105C, General Purpose, 1600V@85C, Lead Spacing=22.5 mm



## Dimensions (mm)

## Specifications

| ID | Dimension | Tolerance | Manufacturer:                | KEMET             |
|----|-----------|-----------|------------------------------|-------------------|
| L  | 26.5      | +0.3      | Brand:                       | Arcotronics       |
| H  | 15        | +0.1      | Capacitance:                 | 0.01 uF           |
| T  | 6         | +0.2      | Temperature Range:           | -55/+105C         |
| S  | 22.5      | +/-0.4    | Rated Temperature:           | 85C               |
| LL | 4         | +2        | Voltage @ rated temp:        | 1600V             |
| F  | 0.8       | +/-0.05   | Voltage AC:                  | 700VAC            |
|    |           |           | Tolerance:                   | +/-10%            |
|    |           |           | Body Type:                   | Radial Box        |
|    |           |           | Construction:                | Double Metallized |
|    |           |           | Application:                 | General Purpose   |
|    |           |           | Sub Application:             | Pulse             |
|    |           |           | Dissipation Factor @ 10 kHz: | 0.06%             |
|    |           |           | Dissipation Factor @ 100kHz: | 0.1%              |
|    |           |           | Insulation Resistance:       | 100 GOhm          |
|    |           |           | Inductance:                  | 18 nH             |
|    |           |           | Maximum dVdT:                | 4500v/us          |
|    |           |           | Maximum K0:                  | 1400000V^2/us     |
|    |           |           | Package Kind:                | Bulk              |
|    |           |           | Package Type:                | Bag               |
|    |           |           | Package Quantity:            | 805               |