

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [78492-0001](#)
Status: **Active**
Overview: Micro Serial ATA Connectors
Description: 1.27mm Pitch Micro Serial ATA Device Receptacle for 45.72mm SSD/HDD, SMT, Vertical, with Pegs and Kapton Tape, 16 Circuits, Embossed Tape on Reel, 0.127µm Gold (Au) Plating, Lead-Free

Documents:

[3D Model](#) [Product Specification PS-78492-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR19980
 UL E29179

General

Product Family PCB Receptacles
 Series [78492](#)
 Application Board-to-Board, Signal
 Comments Rimmed connector base; connector width: 4.38mm
 Overview [Micro Serial ATA Connectors](#)
 Product Name Micro Serial ATA, Serial ATA
 UPC 883906913120

Physical

Circuits (Loaded) 16
 Circuits (maximum) 16
 Color - Resin Black
 Durability (mating cycles max) 500
 Flammability 94V-0
 Glow-Wire Compliant No
 Guide to Mating Part Yes
 Keying to Mating Part Yes
 Lock to Mating Part No
 Material - Metal Copper Alloy
 Material - Plating Mating Gold
 Material - Plating Termination Tin
 Material - Resin High Temperature Thermoplastic
 Net Weight 0.746/g
 Number of Rows 1
 Orientation Vertical
 PCB Locator Yes
 PCB Retention Yes
 Packaging Type Embossed Tape on Reel
 Pitch - Mating Interface 1.27mm, 1.32mm
 Pitch - Termination Interface 1.27mm, 1.32mm
 Plating min - Mating 0.127µm
 Plating min - Termination 2.540µm
 Polarized to Mating Part Yes
 Polarized to PCB Yes
 Stackable No
 Temperature Range - Operating 0°C to +55°C
 Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 1.5A




image - Reference only

EU RoHS

ELV and RoHS Compliant
REACH SVHC Contains SVHC: No
Low-Halogen Status Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[78492Series](#)

Mates With

[78103](#) , [78283](#) and [78285](#) Micro SATA Device Plugs

Grounding to PCB	Yes
Voltage - Maximum	30V

Solder Process Data

Duration at Max. Process Temperature (seconds)	3
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Product Specification	PS-78492-001
Sales Drawing	SD-78492-001

This document was generated on 12/04/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION