



**Notes**

Note Only required when using relays without integrated status indicator!

## Technical data

### Operating Data

Nominal operating voltage	AC 230 V
Current consumption at U <sub>N</sub>	1.6 mA

### Signaling

Status indicator	Red LED
------------------	---------

## Mechanical Data

Mounting type	Pluggable module
---------------	------------------

## Material Data

Fire load	0.033 MJ
Weight	1.6 g

## Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-37-16-92
eCl@ss 9.0	27-37-16-92
ETIM 8.0	EC002586
ETIM 7.0	EC002586
PU (SPU)	50 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454484644
Customs tariff number	85318070000

## Approvals / Certificates

### General approvals



Approval	Standard	Certificate Name
EAC Brjansker Zertifizierungs- stelle	TP TC 004/2011	EAC RU C-DE.AM02. B.00122/19

## Downloads

### Environmental Product Compliance

#### Compliance Search

Environmental Product  
Compliance 788-125



## Documentation



Bid Text			
788-125	19.02.2019	xml 2.49 KB	↓
788-125	20.02.2019	docx 15.02 KB	↓

CAD/CAE-Data	
<b>CAD data</b>	<b>CAE data</b>
2D/3D Models 788-125	EPLAN Data Portal 788-125
↓	↓
	WSCAD Universe 788-125
	↓
	ZUKEN Portal 788-125
	↓