


7933A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable



For more Information
please call

1-800-Belden1



Description:

24 AWG Bonded-Pairs solid bare copper conductors, polyolefin insulation, overall Beldfoil® shield (100% coverage) with drain wire, .030" industrial grade sunlight- and oil-resistant PVC jacket, drain wire. Sequential marking at two foot intervals.

Usage (Overall)

Suitable Applications:

Industrial Ethernet, Harsh Environments, 200MHz Category 5e, M-12 Compatible, 100Base TX, 100BaseVG ANYLAN, 155A TM, 622A TM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, RJ-45 Compatible, EtherNet/IP

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 2 | 24 | Solid | BC - Bare Copper |

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | 7x32 | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|---|
| Industrial Grade PVC - Polyvinyl Chloride |

Overall Cable

Overall Nominal Diameter: 0.235 in.

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Orange Stripe & Orange |
| 2 | White/Green Stripe & Green |

Mechanical Characteristics (Overall)

Storage Temperature Range: -40°C To +85°C

Installation Temperature Range: -25°C To +75°C

Operating Temperature Range: -40°C To +75°C

Bulk Cable Weight: 30 lbs/1000 ft.

7933A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

| | |
|--|-----------|
| Max. Recommended Pulling Tension: | 20 lbs. |
| Min. Bend Radius (Install)/Minor Axis: | 0.500 in. |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|---|
| NEC/(UL) Specification: | CMR, UL 444 |
| CEC/C(UL) Specification: | CMR |
| Other Standards: | 11801 Category 5 |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | 568-B.2 Category 5e |
| Other Specification: | NEMA WC-63.1 Category 5e, UL verified to Category 5e, EtherNet/IP Compliant |

Flame Test

| | |
|-----------------|--------------|
| UL Flame Test: | UL1666 Riser |
| CSA Flame Test: | FT4 |

Suitability

| | |
|------------------------|-----|
| Suitability - Outdoor: | Yes |
| Sunlight Resistance: | Yes |
| Oil Resistance: | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)
15

Maximum Capacitance Unbalance (pF/100 m): 150

Nominal Velocity of Propagation:

VP (%)
70

Maximum Delay:

Delay (ns/100 m)
538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)
45

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
9.38

Max. Operating Voltage - UL:

Voltage
300 V RMS

7933A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

Maximum DCR Unbalanced:

| DCR Unbalance @ 20°C (%) |
|--------------------------|
| 3 |

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1 | 2.0 | 65.3 | 62.3 | 63.0 | 60.0 | 20.0 | 23 |
| 4 | 4.1 | 56.3 | 53.3 | 51.0 | 49.0 | 23.6 | 23.0 |
| 8 | 5.8 | 51.8 | 48.8 | 46.0 | 43.0 | 25.4 | 24.5 |
| 10 | 6.5 | 50.3 | 47.3 | 43.0 | 41.0 | 26.0 | 25.0 |
| 16 | 8.2 | 47.3 | 44.3 | 39.0 | 36.0 | 26.0 | 25.0 |
| 20 | 9.3 | 45.8 | 42.8 | 36.5 | 33.5 | 26.0 | 25.0 |
| 25 | 10.4 | 44.3 | 41.3 | 33.9 | 30.9 | 25.5 | 24.3 |
| 31.25 | 11.7 | 42.9 | 39.9 | 31.0 | 28.0 | 25.0 | 23.6 |
| 62.5 | 17.0 | 38.4 | 35.4 | 22.0 | 19.0 | 23.5 | 21.5 |
| 100 | 22.0 | 35.3 | 32.3 | 14.0 | 11.0 | 22.5 | 20.1 |
| 155 | 28.1 | 32.5 | 29.5 | 4.4 | 1.4 | 15.8 | |
| 200 | 32.0 | 30.8 | 27.8 | 4.0 | 1.0 | 15.0 | |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1 | 100 ± 15 | 102.5 ± 7.5 | 63.8 | 60.8 |
| 4 | 100 ± 15 | 102.5 ± 7.5 | 51.7 | 48.7 |
| 8 | 100 ± 15 | 101 ± 6 | 45.7 | 42.7 |
| 10 | 100 ± 15 | 101 ± 6 | 43.8 | 40.8 |
| 16 | 100 ± 15 | 101 ± 6 | 39.7 | 36.7 |
| 20 | 100 ± 15 | 101 ± 6 | 37.7 | 34.7 |
| 25 | 100 ± 15 | 101 ± 6 | 35.8 | 32.8 |
| 31.25 | 100 ± 15 | 101 ± 6 | 33.9 | 30.9 |
| 62.5 | 100 ± 15 | 101 ± 6 | 27.8 | 24.8 |
| 100 | 100 ± 15 | 101 ± 6 | 23.8 | 20.8 |
| 155 | 100 ± 25 | 100 ± 15 | 19.9 | 16.9 |
| 200 | 100 ± 25 | 100 ± 15 | 17.7 | 14.7 |

Notes (Overall)

Notes: U. S. Patents 5, 606, 151 and 5, 734, 126. EtherNet IP is a trademark of ControlNet International Ltd. under license by DeviceNet Vendor Association, Inc. Operating Temperature subject to length de-rating.

Notes (Cont'd.): Cable passes -40C Cold Bend per UL 1581.

Related Documents:

No related documents are available for this product

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|----------|-------|----------------------|
| 7933A 0101000 | 1,000 FT | 32.000 LB | BLACK | C | 2 PR #24 PP FS FRPVC |
| 7933A 0102000 | 2,000 FT | 64.000 LB | BLACK | C | 2 PR #24 PP FS FRPVC |
| 7933A 1NH1000 | 1,000 FT | 33.000 LB | TEAL 1NH | C | 2 PR #24 PP FS FRPVC |

Notes:
C = CRATE REEL PUT-UP.

Revision Number: 9 Revision Date: 05-14-2007

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express,

7933A Multi-Conductor - Category 5e DataTuff® Twisted Pair Cable

statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.