



expansion module PROFIBUS DP plug-in, for 7KM PAC3200 / 3220 4200 / 3VA COM100 / 800

| Model  |  |                                  |
|--|--|----------------------------------|
| product brand name   | SENTRON                                    |                                  |
| product designation  | PROFIBUS DP expansion module               |                                  |
| type of voltage supply   | via PAC 3200 / PAC4200 / COM100 / 800      |                                  |
| General technical data   |  |                                  |
| MTBF   | 141.1 y                                    |                                  |
| galvanic isolation   | Maximum insulation voltage: 500V AC        |                                  |
| reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 | P  |                                  |
| degree of pollution  | 2 according to IEC 61131                   |                                  |
| Protection class   |  |                                  |
| protection class IP  | IP20                                       |                                  |
| combustibility class according to UL 94  | V 0  |                                  |
| suitability for use  | 7KM PAC 3200 / PAC 4200 / 3VA COM100 / 800 |                                  |
| <ul style="list-style-type: none"> <li>reactive power meter</li> </ul>                         | No   |                                  |
| Connections  |  |                                  |
| type of electrical connection  | 9-pole Sub-D plug according to IEC 61158   |                                  |
| Mechanical Design  |  |                                  |
| height   | 63 mm                                      |                                  |
| width  | 43 mm                                      |                                  |
| depth  | 22 mm                                      |                                  |
| fastening method   | pluggable                                  |                                  |
| Environmental conditions   |  |                                  |
| ambient temperature / during operation   |  |                                  |
| <ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>                     | -5 °C<br>55 °C                             |                                  |
| ambient temperature / during storage   |  |                                  |
| <ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>                     | -25 °C<br>70 °C                            |                                  |
| Certificates   |  |                                  |
| reference code / according to EN 61346-2   | P  |                                  |
| <b>General Product Approval</b>  | <b>EMC</b>                                 | <b>Declaration of Conformity</b> |

[Confirmation](#)

[KC](#)



[Environmental Confirmations](#)

[Miscellaneous](#)



**Further information**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KM9300-0AB01-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7KM9300-0AB01-0AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7KM9300-0AB01-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM9300-0AB01-0AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



