

Cotton Tipped Applicator

Wood shaft



- USP Grade Cotton Tip

- Northern Maine White Birch Shaft

Actual Size

Description

This absorbent cotton tipped applicator is produced with High Quality USP grade cotton which is carded and coiled onsite to maintain consistency. It is bonded securely to a rigid white birch shaft by an aqueous based adhesive.

Dimensions

6" Overall Length (152.4mm)

Tip

- .188" Dia. (4.78mm)
- .625" Length (15.88mm)

Shaft

- .100" Dia. (2.54mm)
- 5.812" Length (147.62mm)

Standards

- CE marked for medical use
- ISO 9001:2008
- ISO 13485:2003
- FDA GMP's

Qualities

- Medical grade quality
- Absorbent tip
- Soft smooth tip

Applications

Medical

- Applying salves or ointments
- Wound care
- Specimen collection

Industrial

- Applying adhesives or other liquids
- Removing dirt, contamination, fluxes or resins
- Cleaning with IPA or other solvents

Ref #	Packaging
806-WC	10/10/100 (10 boxes per case, 10 bags per box, 100 swabs per bag)
806-WCB	100/100 bulk (100 bags per case, 100 swabs per bag)



Quality Medical Products Since 1919

Puritan Medical Products Company LLC
Guilford, Maine 04443-0149 USA

Tel 800-321-2313 (US and Canada Only)
207-876-3311

Fax 800-323-4153
207-876-3130

Web www.puritanmedproducts.com

Email sales@puritanmedproducts.com

1-800-321-2313
puritanmedproducts.com

Cotton Tipped Applicator

Wood Shaft

806-WC / 806-WCB

NVR

NON-VOLATILE RESIDUE

Test method IDEMA method M7-98

NVR Solvent - Hexane

NVR 12 µg/swab

The minimum detection limit for NVR is 10 µg/swab

ION CHROMATOGRAPHY TESTING RESULTS

IONIC CLEANLINESS

Test method IDEMA M13-99 (anions) M12-99 (cations)

ANIONS

Fluoride	ND
Chloride	0.9000 µg/swab
Nitrate	ND
Bromide	2.5000 µg/swab
Nitrate	0.3250 µg/swab
Sulfate	4.3000 µg/swab
Phosphate	11.2500 µg/swab

CATIONS

Lithium	ND
Sodium	10.8000 µg/swab
Ammonium	0.7500 µg/swab
Potassium	13.7550 µg/swab
Magnesium	2.7450 µg/swab
Calcium	6.8250 µg/swab

ND - Non Detected

Test procedures available upon request.