

For more Information  
please call

1-800-Belden1

## Description:

Twinax, 24 AWG stranded (19x36) .024" silver-coated high-strength copper alloy conductor, TFE Teflon® insulation, SC high strength CA braid shield (93% coverage), PFA jacket.

## Physical Characteristics (Overall)

### Conductor

#### AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	24	19x36	SCHSCA - Silver Coated High Strength Copper Alloy	.024

### Insulation

#### Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Teflon®	TFE - Tetrafluoroethylene	.084

### Outer Shield

#### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	SCHSCA - Silver-Coated High Strength Copper Alloy	93

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material
PFA

### Overall Cable

Overall Nominal Diameter: 0.129 in.

## Mechanical Characteristics (Overall)

Operating Temperature Range: -55°C To +200°C

UL Temperature Rating: 200°C

Bulk Cable Weight: 15 lbs/1000 ft.

Max. Recommended Pulling Tension: 12 lbs.

Min. Bend Radius (Install)/Minor Axis: 2.500 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL2P

EU Directive 2002/95/EC (RoHS): No

Military Specification: MIL-C-17, M17/176-00002, MIL-STD-1553 DATA BUS CABLE

### Flame Test

UL Flame Test: NFPA 262

### Plenum/Non-Plenum

Plenum (Y/N): Yes

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)
77

### Nom. Inductance:

Inductance (µH/ft)
.118

**Max. Mutual Capacitance:**

Capacitance (pF/ft)
24.0

**Maximum Capacitance Unbalance:**

Description	Capacitance (pF/ft)
	5

**Nominal Velocity of Propagation:**

VP (%)
70

**Nominal Delay:**

Delay (ns/ft)
1.62

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
7.3

**Nom. Attenuation:**

Freq. (MHz)	Attenuation (dB/100 ft.)
1	1.2
10	4.0
50	9.2
100	13.0
200	18.4
400	26.1
700	34.6
900	39.3
1000	41.4

**Max. Attenuation:**

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100 ft.)
	1			1.4

**Max. Operating Voltage - UL:**

Voltage
150 V RMS

## Notes (Overall)

**Notes:** Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
81553 0061000	1,000 FT	18.000 LB	BLUE, LIGHT	F Z	2#24 TFE BRD PFA
81553 006500	500 FT	9.000 LB	BLUE, LIGHT	F Z	2#24 TFE BRD PFA

**Notes:**

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 3      Revision Date: 03-30-2012

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract,

## 81553 Twinax - Twinax

negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.  
All sales of Belden products are subject to Belden's standard terms and conditions of sale.