

Pushbutton Ø 19 mm silver contact

82-5151.2000



<https://eao.com/p/82-5151.2000>

Your product:



82-5151.2000 Pushbutton Ø 19 mm silver contact

FRONT

Front bezel material: Stainless steel

MOUNTING

Mounting cut-out: Ø 19 mm

OPERATING-/INDICATION PART

Lens optics: opaque

Lens material: Stainless steel

Lens colour: Silver

Lens illumination: non illuminative

Lens shape: flush

ELECTRICAL CHARACTERISTICS

Electrical lifetime: 50 000 cycles of operation

Switching voltage and switching current:

according to IEC 60947-5-1 (Silver contacts)	
Service categorie AC-15	
Voltage	Current
24 VAC	1 A
35 VAC	1 A (M12 versio
110 VAC	1 A
220 VAC	0.5 A
Switch rating DC service categorie DC-13 (Silver contacts)	
Voltage	Current
24 VDC	0.7 A
35 VDC	0.5 A (M12 vers
110 VDC	0.2 A
220 VDC	0.1 A

according to UL 508 (Silver contacts)

$\cos\phi$ 0,75 ... 0,8

Voltage

120 VAC

240 VAC

24 VAC

Current

5 A

3 A

1 A

Contacts:	1 C
Pollution degree:	2, according to EN IEC 60947-1
Rated insulation voltage U_i:	250 V
Rated Operational Voltage U_e:	250 VAC
Electric strength:	1500 VAC, 50 Hz 1 minute between life terminals and ground
Thermal current I_{th}:	5 A

MECHANICAL CHARACTERISTIC

Contact material:	Silver
Operating Travel:	ca. 3 mm
Weight:	0.018 kg
Switching action:	Maintained
Operating force:	4 N ... 7 N
Switching system:	Snap-action switching element
Terminal:	Soldering terminal, 2.8 x 0.5 mm
Tightening torque:	0.5 ... 0.6 Nm
Mechanical lifetime:	500 000 cycles of operation

AMBIENT CONDITION

Operating temperature:	- 30 °C ... + 70 °C
Vibration resistance:	10 ... 500 Hz, amplitude 1.5 mm p-p according to IEC 60068-2-6
Storage temperature:	- 40 °C ... + 80 °C
Climate resistance:	Damp heat, 21 days according to IEC 60512-11
Shock resistance:	Max. 500 m / s ² as per IEC 60068-2-27

CERTIFICATE


Conformities:	CE, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)
Approbations:	CB, CCC, C UL, UL

OTHER


Short Description:

Pushbutton \varnothing 19 mm silver contact, Maintained, 1 C, Soldering terminal, 2.8 x 0.5 mm, Stainless steel, Silver


Dimension drawings:



Wiring diagrams:



Component layouts:



Mounting cut-outs:

