

826646

- 8

Product Details

Live Product Chat

US Only

8:30am - 5pm ET, Mon - Fri

826646

- 8

Active

.100 inch AMPMODU Headers

Always EU RoHS/ELV Compliant

(

Statement of Compliance

)

Product Highlights:

Header

Header Type = Breakaway

Number of Rows = Single

Number of Positions = 8

Mating Post Length = 5.80 mm

View all Features

|

Find Similar Products

Quick Links

Check Pricing & Availability

Search for Tooling

Product Feature Selector

Contact Us About This Product

Documentation & Additional Information

Product Drawings:

Header

AMPMODU II STIFTLLEISTEN, EINREIHIG

(PDF, German)

Catalog Pages/Data Sheets:

Header

None Available

Product Specifications:

Header

None Available

Application Specifications:

Header

None Available

Instruction Sheets:

Header

None Available

CAD Files:

(

CAD Format & Compression Information

)

2D Drawing

(DXF, Version O)

3D Model

(IGES, Version O)

3D Model

(STEP, Version O)

Additional Information:

Header

Product Line Information

Related Products:

Header

Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

Header

Number of Positions = 8

Mount Angle = Vertical

PCB Retention Feature = No

Surface Mount Compatible = No

Board Standoff = Without

Mounting Ears = Without

Mating Connector Lock = Without

Profile = Standard

Mechanical Attachment:

Mating Post Length (mm [in]) = 5.80 [0.228]

Panel Attachment = Without

Termination Related Features:

Termination (Solder) Post Length (mm [in]) = 3.20 [0.126]

Solder Tail Contact Plating = Tin

Body Related Features:

Header Type = Breakaway

Number of Rows = Single

Centerline, Matrix (mm [in]) = 2.54 [.100]

Selectively Loaded = No

Mount Type = PC Board

Contact Related Features:

Contact Mating Area Plating Material = Gold (30)

Contact Material = Phosphor Bronze

Housing Related Features:

Housing Material = Thermoplastic Polyester

Housing Flammability Rating = UL 94V -0

Industry Standards:

RoHS/ELV Compliance = RoHS compliant, ELV compliant

Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C

RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

High Temperature Housing = No

Operation/Application:

High Speed Serial Data Connector = No

Other:

Brand = AMP

Provide Website Feedback

|

Contact Customer Support

Home

|

Customer Support

|

Suppliers

|

Site Map

|

Privacy Policy

|

Browser Support

© 2008 Tyco Electronics Corporation All Rights Reserved