

LOC		DIST		REVISIONS					
—		—		P	LTR	DESCRIPTION	DATE	DWN	APVD
				C		Contact pin base material change from CuSn (Phosphor bronze) to CuZn (Brass). Plating change from MIN. 0.8µm gold plating to min. 0.7µm Pd Ni + 0.1µm gold flash at contact area (Area F).	22JUL2014	TJ	JK

POLZ. PRO REIHE	L±0.4	BESTELL-NR.
—	—	—
2	5.08	829 114 -2
3	7.62	-3
4	10.16	-4
5	12.70	-5
6	15.24	-6
7	17.78	-7
8	20.32	-8
9	22.86	-9
10	25.40	-0
11	27.94	-1
12	30.48	-2
13	33.02	-3
14	35.56	-4
15	38.10	-5
16	40.64	-6
17	43.18	-7
18	45.72	-8
19	48.26	-9
20	50.80	-0
21	53.34	-1
22	55.88	-2
23	58.42	-3
24	60.96	-4
25	63.50	-5
26	66.04	-6
27	68.58	-7
28	71.12	-8
29	73.66	-9
30	76.20	-0
31	78.74	-1
32	81.28	-2
33	83.82	-3
34	86.36	-4
35	88.90	-5
36	91.44	-6
37	93.98	-7
38	96.52	-8
39	99.06	-9
40	101.60	-0
41	104.14	-1
42	106.68	-2
43	109.22	-3
44	111.76	-4
45	114.30	-5
46	116.84	-6
47	119.38	-7
48	121.92	-8
49	124.46	-9
50	127.00	5- 829 114 -0

CONTACT PIN	CuZn	1
PIN HOUSING	PBTP GV	GRÜN
DESCRIPTION	MATERIAL	FINISH/COLOR

STECKSEITE: IM BEREICH "F" 0.7µm PdNi+0.1µm GOLD FLASH ÜBER 1.27µm NICKEL
 LÖTSEITE: MIN. 2.5µm ZINN ÜBER 1.27µm NICKEL

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

DIMENSIONS:		DWN	02.11.88	MATERIAL	FINISH
mm		M.SCHAARSCHMIDT		SEE TABLE	SEE TABLE
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK	25.01.89		
± 0.2		W.SIMONS			
0 PLC ± -		APVD	-		
1 PLC ± -		PRODUCT SPEC	108-18012		
2 PLC ± -		APPLICATION SPEC	-	NAME	
3 PLC ± -				AMPMODU II STIFTLEISTE, ZWEIREIHIG	
4 PLC ± -				SIZE	CAGE CODE
ANGLES ± -				DRAWING NO	RESTRICTED TO
		WEIGHT	-	A4 00779	C-829114
		CUSTOMER DRAWING			SCALE 4:1
					SHEET 1 OF 1
					REV C