

## 8404 Multi-Conductor - Four-Conductor Star Quad, Low-Impedance Cable



For more Information  
please call

1-800-Belden1



### Description:

20 AWG stranded (19x32) high-conductivity tinned copper conductors, polyethylene insulation, rayon braid, tinned copper braid shield (85% coverage), PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
4	20	19x32	High Conductivity TC - Tinned Copper	.037

#### Insulation

##### Insulation Material:

Insulation Material	Wall Thickness (in.)	Dia. (in.)
PE - Polyethylene	.016	.069

#### Outer Shield

##### Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Braid	TC - Tinned Copper	85

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.032

#### Overall Cable

##### Overall Cabling Color Code Chart:

Number	Color
1	Clear
2	Black
3	Red
4	Green

Overall Cabling Separator Material: Rayon Braid

Overall Nominal Diameter: 0.252 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

UL Temperature Rating: 60°C (UL AWM Style 2094)

Bulk Cable Weight: 46 lbs/1000 ft.

Max. Recommended Pulling Tension: 100 lbs.

Min. Bend Radius (Install)/Minor Axis: 2.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

AWM Specification: UL Style 2094 (300 V 60°C)

EU CE Mark: Yes

## 8404 Multi-Conductor - Four-Conductor Star Quad, Low-Impedance Cable

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

**Flame Test**

UL Flame Test:	VW-1
----------------	------

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Electrical Characteristics (Overall)****Nom. Characteristic Impedance:**

Impedance (Ohm)

45

**Nom. Inductance:**

Inductance (µH/ft)

.2

**Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)

23

**Nom. Cap. Between Cond. in a Quad Config.:**

Capacitance (pF/ft)

49

**Nominal Velocity of Propagation:**

VP (%)

66

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

10.2

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

3.23

**Max. Operating Voltage - UL:**

Voltage

300 V RMS (UL AWM Style 2094)

**Max. Recommended Current:**

Current

3.1 Amps per conductor @ 25°C

**Other Electrical Characteristic 1:** 2/c 17 AWG equivalent DCR when connected to a 3-pin XLR.

**Notes (Overall)**

**Notes:** Quad connection scheme: The two blue wires (or wires directly opposite one another) are connected together to form one conductor, and similarly the two white wires (or remaining wires) are connected together to form the second conductor.

**Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

## 8404 Multi-Conductor - Four-Conductor Star Quad, Low-Impedance Cable

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8404 060U1000	1,000 FT	48.000 LB	CHROME		4 #20 PE SHLD PVC
8404 060100	100 FT	5.400 LB	CHROME		4 #20 PE SHLD PVC
8404 0601000	1,000 FT	49.000 LB	CHROME	C	4 #20 PE SHLD PVC
8404 060500	500 FT	23.000 LB	CHROME	C	4 #20 PE SHLD PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 05-14-2007

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.