




NOTES:

1. FOR USE WITH BOEING BMS13-65 OJ & ADAMS RUSSELL FC38Z CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-546-4.
3. FOR CRIMPING USE DIE KTH-2213.
4. INTERFACE PER MIL-STD-348, FIG. 317-1.
5. CENTER CONTACT, 1-843-8MA9, SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: KINGS 845-10-9 (DATE CODE)
7. MATERIALS:
 - K-GRIP SLEEVE: COM. BRONZE, ALLOY ASTM B135
 - GASKET: SIL. RUB., A-A-59588
 - C-RING: PHOS. BRONZE, ASTM B103
 - INSULATOR: TEFLON, ASTM D1710
 - OUTER CONTACT: BER. COP., ASTM B196
 - ALL OTHER METAL PARTS: BRASS, ASTM B16
8. FINISHES:
 - CENTER CONTACT: .000050 MIN GOLD PLATE PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290 (RoHS)
 - OUTER CONTACT: .000200 MIN SILVER PER ASTM B700 OVER .000020 MIN COPPER PER ASTM B734 (RoHS)
 - ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE: 50 OHMS
 - FREQUENCY RANGE: DC TO 4 GHZ
 - WORKING VOLTAGE: 1500 VRMS
10. WEIGHT: 58.1 GRAM

845-10-9

REVISIONS

ISSUE	CHANGES
0	ER 35988 ME 12/12/94
1	ER 36286 E ME 05/16/95
C	REVISED PER DMF304 & ER35797 TZ 11/18/11

CUSTOMER
SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

CAGE CODE: 91836

REF: BOEING

PANEL, HN

DRAWN	MJB	DATE	08/11/94
DESIGN	CT	DATE	08/09/94
APPR.		DATE	

KINGS
by WINCHESTER
ELECTRONICS
Winchester Electronics
62 Barnes Industrial
Road North
Wallingford, CT 06492

845-10-9