


> PN Search


**Straight 2Row Bergstik II Hdr
Retentive Leg**
86380-4NNH
> Communications Data
& Consumer division

FCI brings you more

✉ [Contact our sales/
technical support](#)✉ [Sample request](#)€ [Price request](#)📊 [Check distributor stock](#)➔ [Download](#)📄 [Mating half](#)🔍 [Alternative parts](#)🔧 [Application tooling](#)> [Customer Drawing](#)

Not Available

Not Available

www.foehrenbach.be[Americas](#)[Asia Pacific](#)**Features Selected**

RoHS Lead free Compatible option (recommended)	No
Packaging	Standard Bag
To Specify Number of Positions	Replace NN with total number of positions required
Orientation	Vertical
PCB Attachment Type	Through Hole
No of Rows	2
Contact Area Plating	Tin/Lead
Mating Post Length (in.)	0.25
Solder Tail Length (in.)	0.12
Solder Tail Retention?	Yes

Other Properties

Number of Positions Available	NN (in resulting part number) = 02 through 72 (Even)
Lead free, RoHS replacement number	86380-4nnHLF
OA Pin Length (in.)	0.47
High Temperature Plastic YorN	yes
Solder Tail Plating	Tin/lead
Contact Base Metal	Phosphor Bronze
Color	Black
Applicable Soldering Processes	IR reflow
Insulation Resistance	5000 M ohms
Withstanding Voltage	1500 V ac rms
Current Rating	3 amp continuous
Retention Force	8.88 N (2 lbf)
Temperature Range	-65 °C to +130 °C
Application Equipment	HT-0320

[Home page](#)**Product quick search**

P/N Search

FCI

Competitor

GORoHS/LF P/N
Search

Product type search

Alphabetical list

Connection type

Markets / Applications

[Product finder](#)[Literature](#)[Services](#)[Contact us](#)**Registered users**[Forgot password ?](#)[Register now](#)

Trademark	BergStik ®
Approvals & Certification	UL and CSA approved
Mating Data	Mates with 0.64 mm (0.025 in.) compatible receptacles on 2.54 mm (0.100 in.) centerlines
Literature	Standard Products Catalog
Comments	Custom polarization available. Tube packaging available on selected part numbers.