

Data Sheet | Item Number: 870-405

Jumper; 5-way; insulated; light gray

<https://www.wago.com/870-405>



Color: ■ light gray

Electrical data

Ratings per IEC/EN

Rated current 18 A

Ex information

Rated current (Ex e II) 13.5 A

Physical data

| | |
|-------------------|-----------------------|
| Width | 24 mm / 0.945 inches |
| Height | 2.5 mm / 0.098 inches |
| Jumper assignment | 1-2-3-4-5 |

Material data

Note (material data)

[Information on material specifications can be found here](#)

| | |
|-----------|------------|
| Color | light gray |
| Fire load | 0.021 MJ |
| Weight | 2.3 g |

Commercial data

| | |
|-----------------------|--|
| Product Group | 16 (Rail Mounted Terminal Blocks with CCC) |
| eCl@ss 10.0 | 27-14-11-40 |
| eCl@ss 9.0 | 27-14-11-40 |
| ETIM 8.0 | EC000489 |
| ETIM 7.0 | EC000489 |
| PU (SPU) | 25 (25) pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4066966271737 |
| Customs tariff number | 85366990990 |

Environmental Product Compliance

| | |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Downloads

Environmental Product Compliance

| | |
|--|---|
| Compliance Search | |
| Environmental Product Compliance 870-405 | ↓ |

Documentation

| | | |
|------------------------|-------------------|---|
| Additional Information | | |
| Technical Section | pdf 2240.62 KB | ↓ |

| | | | |
|----------|------------|-----------------|---|
| Bid Text | | | |
| 870-405 | 19.02.2019 | xml 2.51 KB | ↓ |
| 870-405 | 04.01.2018 | doc 23.50 KB | ↓ |



CAD/CAE-Data

| | |
|----------------------|---|
| CAD data | |
| 2D/3D Models 870-405 | ↓ |

| | |
|---------------------------|---|
| CAE data | |
| EPLAN Data Portal 870-405 | ↓ |
| WSCAD Universe 870-405 | ↓ |
| ZUKEN Portal 870-405 | ↓ |

Installation Notes

Commoning



Commoning with push-in type jumper bars:
Two parallel jumper slots are accommodated in one terminal block.

Push jumper bars down firmly until fully inserted. When using multipole bars, push alternately on the right and then left side until installed.
Push-in type jumper bars 1 – 3 – 5 – 7 or 1 – – 4 – – 7 upon request