

Device adapter S2, 80 A, short AWG4 25 mm<sup>2</sup> 150 mm 150° Length 200 mm, Width 54 mm



Model	
product brand name	SENTRON
Product designation	Device adapter
Design of the product	Accessories
Operating current / at AC / rated value	80 A
Operating voltage / at AC / rated value	690 V
suitability for use	SIRIUS S2

Connections	
Type of connectable conductor cross-sections / for copper conductor / stranded	25 mm <sup>2</sup> , AWG 4

Mechanical Design	
length	200 mm
Busbar center-to-center spacing	60 mm
net weight	508 g

Certificates	
--------------	--

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------



[Miscellaneous](#)

[Special Test Certificate](#)

[Miscellaneous](#)

Test Certificates	Shipping Approval
-------------------	-------------------

[Type Test Certificates/Test Report](#)



Shipping Approval	other	Railway
-------------------	-------	---------



[Confirmation](#)

[Miscellaneous](#)

[Vibration and Shock](#)

Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1261-5MS13>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8US1261-5MS13>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8US1261-5MS13](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1261-5MS13)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



