

**KT-F 36****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

- Suitable in situations where cables have to be cut in confined spaces
- Easy handling
- Minimal manual force required
- Release option in every cutting position
- Not suitable for steel wires, steel-armoured cables, aluminium alloys and hard-drawn copper conductors
- Do not cut live conductors

**General ordering data**

Version	Cutting tools, Front cutter
Order No.	<a href="#">9002 190000</a>
Type	KT-F 36
GTIN (EAN)	4008 190066345
Qty.	1 pc(s).

Creation date January 26, 2023 11:41:29 AM CET

Catalogue status 24.01.2023 / We reserve the right to make technical changes.

## KT-F 36

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Depth	50 mm	Depth (inches)	1.969 inch
Height	150 mm	Height (inches)	5.905 inch
Width	360 mm	Width (inches)	14.173 inch
Net weight	1,642.78 g		

## Technical data

Description of article	Front cable cutter for up to 35 mm outer diameter	Version	One-hand mechanical
------------------------	---	---------	---------------------

## Cutting tools

Cable type	Copper and aluminium cables	Copper cable - flexible, max.	300 mm <sup>2</sup>
Copper cable - flexible, max. (kcmil)	600 kcmil	Copper cable - stranded, max.	300 mm <sup>2</sup>
Copper cable - stranded, max. (kcmil)	600 kcmil	Copper cable, max. diameter	35 mm
Max. conductor diameter	36 mm	Stranded aluminium cable, max (mm <sup>2</sup> )	300 mm <sup>2</sup>
Stranded aluminium cable, max. (kcmil)	600 kcmil	Stranded aluminium cable, max. diameter	35 mm

## Classifications

ETIM 6.0	EC000142	ETIM 7.0	EC000142
ETIM 8.0	EC000142	ECLASS 9.0	21-04-47-01
ECLASS 9.1	21-04-90-11	ECLASS 10.0	21-04-47-01
ECLASS 11.0	21-04-47-01	ECLASS 12.0	21-04-47-01

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

## Approvals

Approvals



## Downloads

User Documentation	<a href="#">Manual</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	




**Data sheet**

**KT-F 36**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

-  Cu + Al: max. 35 mm
-  Cu: max. 300 mm<sup>2</sup>  
Al: max. 300 mm<sup>2</sup>
-  Cu: max. 300 mm<sup>2</sup>