

POWERSTRIPPER 6,0**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- for automatic stripping of individual wires
- stripping of flexible wires according to DIN VDE 0295, Cl. 5
- Partial stripping of insulation, the isolation remains on wire end
- Change of tools not necessary
- Quick and easy setting for the proper cross-section
- Stripping length from 3 to 20 mm
- Min. conductor length: 22 mm + stripping length
- Electric drive

General ordering data

Version	Tools, Automatic stripper
Order No.	9028510000
Type	POWERSTRIPPER 6,0
GTIN (EAN)	4008190860752
Qty.	1 pc(s).

Creation date January 3, 2023 10:15:33 AM CET

Catalogue status 16.12.2022 / We reserve the right to make technical changes.

POWERSTRIPPER 6,0**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	295 mm	Depth (inches)	11.614 inch
Height	190 mm	Height (inches)	7.48 inch
Width	190 mm	Width (inches)	7.48 inch
Net weight	8,962 g		

Automatic stripping

Conductor length, min.	22 mm + stripping length		
Connection values	46 VA		
Drive	electrical		
Electrical connection	100-240 V / 50/60 Hz / 70 VA		
Outer diameter of conductor	max.	5 mm	
Pull-off length	3-20 mm		
Pulse time	approx. 0.5 s		
Stripping range	0.05 - 6.0 mm ² (~AWG 30-10)		

Classifications

ETIM 6.0	EC002778	ETIM 7.0	EC002778
ETIM 8.0	EC002778	ECLASS 9.0	17-13-01-01
ECLASS 9.1	17-13-01-02	ECLASS 10.0	17-13-01-02
ECLASS 11.0	17-13-01-01	ECLASS 12.0	17-13-01-01

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	WSCAD
User Documentation	Manual
Catalogues	Catalogues in PDF-format
Brochures	

POWERSTRIPPER 6,0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

