

# 9070KL300D3

## INDUSTRIAL CONTROL TRANSFORMER

### 300VA 208V PRIMARY WITH 610mm/24INCH LEADS



#### Main

Product or component type	Industrial Control Transformer
Range of product	KL

#### Complementary

Phase	1 phase
Rated power in VA	300 VA
Primary voltage	208 V
Secondary voltage	120 V
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Connector type	Lead 2001.31 ft (610 m)

#### Environment

Product certifications	CSA UL Listed CE
NEMA degree of protection	Not rated (open device)
Insulation temperature	266 °F (130 °C)

#### Ordering and shipping details

Category	21692 - 9070 K (NOT KF)
Discount Schedule	CP8
GTIN	00785901939665
Nbr. of units in pkg.	1
Package weight(Lbs)	8.2 lb(US) (3.72 kg)
Returnability	No
Country of origin	US

#### Packing Units

Package 1 Height	6.00 in (15.240 cm)
Package 1 width	7.50 in (19.050 cm)
Package 1 Length	6.50 in (16.510 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------