



Main

Product or component type	Industrial Control Transformer
Power Rating	75 VA
Primary Voltage	208/240/277/380/480 V
Secondary Voltage	24 V
Type	T

Complementary

Number of Phases	1 phase
Power Rating	75 VA
Primary to Secondary Voltage	208/240/277/380/480 V 24 V
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Maximum Height	2.89 in (73.41 mm)
Maximum Width	3.38 in (85.85 mm)
Maximum Depth	3.34 in (84.84 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC23

Environment

Product certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
Enclosure Type	Not rated (open device)
Insulation temperature	221 °F (105 °C)

Ordering and shipping details

Category	16200 - 9070 T (NOT TF) 50-200VA
Discount Schedule	CP8
GTIN	00785901907244
Nbr. of units in pkg.	1
Package weight(Lbs)	6.2 lb(US) (2.81 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	7.10 in (18.034 cm)
Package 1 width	6.30 in (16.002 cm)
Package 1 Length	5.50 in (13.970 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	10 Years
----------	----------