



by Schneider Electric

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	Commercialised
Range of product	9080LB
Product or component type	Miniature Power Distribution Block
[In] rated current	90 A aluminium 115 A copper
Product certifications	CE CSA RoHS UL listed
Material	Thermoplastic block
[Ue] rated operational voltage	600 V AC
Number of poles	3
Number of terminals	1 main 1 branch
Electrical connection	Lugs tin plated aluminium
Number of cables	1 14...2 AWG copper or aluminium main 1 14...2 AWG copper or aluminium branch
Short-circuit current	65 kA

Ordering and shipping details

Category	21711 - 9080 LB
Discount Schedule	CP1
GTIN	00785901097426
Nbr. of units in pkg.	1
Package weight(Lbs)	0.22
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0620 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.