




- Products
- Industries
- Resources
- About TE
- My Account
- Innovation
- Support Center

Home > Products > Tubing & Harnessing > Product Feature Selector > Product Details

# RBK-ILS-125-NR2-0-50MM Product Details

- Share
- Print
- Email



Active

## Heat Shrink Tubing

RBK-ILS-125-NR2-0-50MM

**RBK-ILS-125-NR2-0-50MM**

TE Internal Number: 0989076002

### Product Highlights [View All](#)

- Heat Shrinkable Tubing
- Product Name = RBK-ILS-125
- Product Source = Czech Republic
- Semirigid
- Thin Wall Style

- Pricing & Availability
- Request Sample
- Add to My Part List
- Buy Product through Distributor

### Catalog Pages/Data Sheets

[RBK-ILS Pages from 1654296-3](#) (PDF, English)

### Product Specifications

#### Product Specification

[RBK-ILS-125-0](#) (PDF, English)

### Product Environmental Compliance

#### Safety Data Sheet

- [Aliphatic polyamide based adhesives.](#) (PDF, Dutch)
- [Aliphatic polyamide based adhesives.](#) (PDF, English)
- [Aliphatic polyamide based adhesives.](#) (PDF, French)
- [Aliphatic polyamide based adhesives.](#) (PDF, German)
- [Aliphatic polyamide based adhesives.](#) (PDF, Italian)
- [Aliphatic polyamide based adhesives.](#) (PDF, Spanish)
- [Aliphatic polyamide based adhesives.](#) (PDF, Swedish)

**Please Note:**  
Use the Product Drawing for all design activity

Product Type Features		Environmental	
<b>Product Type</b> <a href="#">?</a> Help information about Product Type	Heat Shrinkable Tubing	<b>Fluid Resistance</b>	Moisture/Spray
<b>Color</b>	Black	<b>Operating Temperature (°C)</b> <a href="#">?</a> Help information about Operating Temperature (°C)	-40 - +125
Dimensions		Conditions for Usage	
<b>Expanded ID, Min. (mm [in])</b> <a href="#">?</a> Help information about Expanded ID, Min. (mm [in])	7.50 [0.295]	<b>Full Recovery Temperature (°C)</b>	135
<b>Recovered ID, Max. (mm [in])</b> <a href="#">?</a> Help information about Recovered ID, Max. (mm [in])	1.65 [0.065]	<b>Shrink Temperature, Min. (°C)</b>	110
<b>Cut Length (mm [in])</b> <a href="#">?</a> Help information about Cut Length (mm [in])	50.00 [1.970]	<b>High Temperature Compatible</b>	No
		Operation/Application	
		<b>Emission Free</b>	No
		<b>Product Use</b>	Wire Splices
		<b>Application</b>	Insulation and Protection



### Related Products


Not quite the product you're looking for?

[Find Similar Products](#)

[View Part in Product Feature Selector](#)

[Check for Tooling](#)

Body Features		Packaging Features	
<b>Product Name</b>	RBK-ILS-125	<b>Packaging Method</b>	Piece
<b>Pliancy</b>	Semirigid	<b>Product Availability</b>	
<b>Wall Style</b>  <b>Help information about Wall Style</b>	Thin	<b>Product Source</b>	Czech Republic
<b>Wall Type</b>  <b>Help information about Wall Type</b>	Dual	<b>Other</b>	
<b>Lining Type</b>  <b>Help information about Lining Type</b>	Adhesive	<b>Brand</b>	Raychem
<b>Material</b>	Crosslinked Polyolefin		
<b>Shrink Ratio</b>  <b>Help information about Shrink Ratio</b>	4:1		
<b>Fluid Type</b>	Water		
<b>Resistant To</b>	Abrasion		
<b>Wall Thickness - Full Recovery (Nominal) (mm [in])</b>	1.40 [0.0551]		
Housing Features			
<b>Material Systems</b>	No		
Industry Standards			
<b>Government/Industry Qualification</b>	No		
<b>Flammability Rating</b>	Flame-Retardant		
<b>UL Rating</b>	None		
<b>CSA Certified</b>	No		
<b>Approved Standards</b>	None		
<b>RoHS/ELV Compliance</b>  <b>Help information about RoHS/ELV Compliance</b>	RoHS compliant, ELV compliant		
<b>Lead Free Solder Processes</b>  <b>Help information about Lead Free Solder Processes</b>	Not relevant for lead free process		
<b>RoHS/ELV Compliance History</b>	Always was RoHS compliant		
<b>Product Compliance</b>			

 Always EU RoHS/ELV Compliant 

These products comply with the substance restrictions of the Restriction on Hazardous Substances Directive 2011/65/EU (RoHS2). These products also comply with the End of Life Vehicles Directive 2000/53/EC (ELV). The RoHS2 Directive requires certain electrical and electronic products be free (except for trace impurities) of mercury, cadmium, hexavalent chromium, PBB, PBDE and lead. Certain exemptions are allowed such as lead used as an alloying additive in copper, steel and aluminum. Finished electrical and electronic products will be CE marked as required by Directive 2011/65/EU (RoHS2). Components may not be CE marked.

**EU RoHS/ELV Compliance**

 **Statement of Compliance**

[View All Product Compliance](#) 

**Corporate Information**

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [Global Accessibility Statement](#)

**Quick Links**

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

**Customer Support**

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

**Keep Me Informed**



