

Product data sheet

Miniature connectors



Product description **M16 IP67 Female cable connector, Contacts: 6 (06-a), 4.1-7.8 mm, unshielded, solder, IP67, UL, Short version**


Area **M16 IP67 series 423**

Part no. **99 5122 40 06**


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 5122 40 06
Connector design	Female cable connector
Version	Connector socket straight
Connector locking system	screw
Termination	solder
Degree of protection	IP67
Cross-sectional area	max. 0.75 mm ² / AWG 18
Cable outlet	4.1-7.8 mm
Temperature range from/to	-30 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Additional information	Short version
Weight (g)	35.45
Customs tariff number	85369010

Electrical parameters

Rated voltage	250 V
Rated impulse voltage	1500 V
Rated current (40 °C)	5.0 A
Insulation resistance	≥ 10 ¹⁰ Ω
Pollution degree	1
Overvoltage category	I
Insulating material group	III
EMC compliance	unshielded

Product data sheet

Miniature connectors

Product description	M16 IP67 Female cable connector, Contacts: 6 (06-a), 4.1-7.8 mm, unshielded, solder, IP67, UL, Short version
Area	M16 IP67 series 423
Part no.	99 5122 40 06

Material

Housing material	CuZn (Brass nickel plated)
Contact body material	PBT (UL94 V-0)
Contact material	CuSn (bronze)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	33934a1d-dc9a-40bb-a9d5-4829109c9ebf

Authorization/approvals

Approvals	UL
-----------	----

Classifications

eCl@ss 11.1	27-44-01-02
ETIM 7.0	EC002635

Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60204-1:2018;EN 60529:1991)
-----------------------	--

Assembly instructions

1. Bead pressing screw, seal and clamping device.
2. Dismantle cable to 17 mm length.
3. Strip and solder single wires.
4. Mount clamping device.
5. Tighten pressing screw.

The diagram illustrates the assembly process for two cable diameters: 4-6 mm and 6-8 mm. Key components shown include the female coupling ring (assembled), female insert, seal, clamping device, male insert, male coupling ring (assembled), and pressing screw. Dimensions are specified as 17 mm for the cable length and 6 mm for the strip length. A torque of 0,8 Nm is indicated for the pressing screw. The cable diameters are labeled as cable-Ø 4-6 mm and cable-Ø 6-8 mm.

Product description	M16 IP67 Female cable connector, Contacts: 6 (06-a), 4.1-7.8 mm, unshielded, solder, IP67, UL, Short version
Area	M16 IP67 series 423
Part no.	99 5122 40 06

General Disclaim Notice

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).