

# Product data sheet

## Miniature connectors




Product description	Female cable connector, Contacts: 5 (05-b), 6.0-8.0 mm, shieldable, solder, IP67, UL
Area	series 423
Part no.	99 5618 19 05


### Illustration



### Scale drawing



### Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

### Technical data

#### General features

Part no.	99 5618 19 05
Connector design	Female cable connector
Version	Connector socket straight
Connector locking system	screw
Termination	solder
Degree of protection	IP67
Cross-sectional area	max. 0.75 mm <sup>2</sup> / AWG 18
Cable outlet	6.0-8.0 mm
Temperature range from/to	-30 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	48.68
Customs tariff number	85369010

#### Electrical parameters

Rated voltage	60 V
Rated impulse voltage	500 V
Rated current (40 °C)	6.0 A
Insulation resistance	≥ 10 <sup>10</sup> Ω
Pollution degree	1
Overvoltage category	I
Insulating material group	III
EMC compliance	shieldable
Shield connection	Shielding ring

#### Material

Housing material	CuZn (Brass nickel plated)
------------------	----------------------------

# Product data sheet

## Miniature connectors



Product description	<b>Female cable connector, Contacts: 5 (05-b), 6.0-8.0 mm, shieldable, solder, IP67, UL</b>
Area	<b>series 423</b>
Part no.	<b>99 5618 19 05</b>

Contact body material	PBT (UL94 V-0)
Contact material	CuSn (bronze)
Contact plating	Au (gold)
REACH SVHC	CAS 96-45-7 (Imidazolidine-2-thione) CAS 7439-92-1 (Lead)
SCIP number	184016c1-e553-4e3c-a754-093ab8dd92a0

### Authorization/approvals

Approvals	UL
-----------	----

### Classifications

eCl@ss 11.1	27-44-01-02
ETIM 9.0	EC002635

### Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60204-1:2018;EN 60529:1991)
-----------------------	--

### Assembly instructions

**1.** Bead pressing screw, pinch ring, seal, distance shell and shield clamping ring on cable.

**2.** Dismantle cable to 20 mm length.

**3.** Strip wires, widen shield and bead shielding ring.

**4.** Solder wires, snap distance shell, push the shield clamping ring and shielding ring together and cut off projecting shielding braid.

**5.** Assemble remaining parts.

**PG 11**

- pressing screw
- pinch ring
- 0,8 Nm
- sleeve
- seal
- shield clamping ring
- shielding ring
- female coupling ring, assembled
- female insert
- distance shell
- strip
- 20
- 4
- 0,8 Nm
- 1,0 Nm
- cable-Ø 8-10 mm
- cable-Ø 8 mm
- cable-Ø 10 mm

**PG 9**

- 0,7 Nm
- 0,9 Nm
- cable-Ø 6-8 mm
- cable-Ø 6 mm
- cable-Ø 8 mm

**PG 7**

- 0,7 Nm
- 0,9 Nm
- cable-Ø 4-6 mm
- cable-Ø 4 mm
- cable-Ø 6 mm
- male coupling ring, assembled
- male insert

Product description	<b>Female cable connector, Contacts: 5 (05-b), 6.0-8.0 mm, shieldable, solder, IP67, UL</b>
-	-
Area	<b>series 423</b>
Part no.	<b>99 5618 19 05</b>

### **Security notices**

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).