

Product data sheet

Characteristics

9998L44

Replacement coil, 110/120 VAC 50/60 Hz,
8903L Contactor, 2 to 6 poles

Product availability: Stock - Normally stocked in distribution facility



Main

Product or component type	Coil
Accessory / separate part destination	Class 8903 contactor

Complementary

[Ue] rated operational voltage	120 V AC 60 Hz 110 V AC 50 Hz
Inrush power in VA	150 VA 140 VA
Average consumption	30 VA
Height	2.38 in (60.5 mm)
Width	2.11 in (53.6 mm)
Depth	1.46 in (37.1 mm)

Ordering and shipping details

Category	21756 - 9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	00785901081210
Package weight(Lbs)	0.16 kg (0.35 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.