# A768MS567M1ELAV017

A768, Polymer Aluminum, 560 uF, 20%, 25 VDC, -55/+125°C




Click here for the 3D model.

| Dimensions | |
|---|---|
| D | 10mm +/-0.5mm |
| L | 12.4mm +/-0.5mm |
| W | 10.3mm +/-0.2mm |
| H | 10.8mm +/-0.2mm |
| C | 11mm +/-0.2mm |
| J | 4.4mm NOM |
| K | 3.2mm NOM |
| P | 4.6mm NOM |
| R | 0.7 - 1.1mm |

| Packaging Specifications | |
|---|---|
| Packaging | T&R, 380mm |

| General Information | |
|---|---|
| Series | A768 |
| Dielectric | Polymer Aluminum |
| Style | SMD Can |
| Description | Surface Mount, Polymer Aluminum |
| RoHS | Yes |
| Lead | V-Chip |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Halogen Free | Yes |

| Specifications | |
|---|---|
| Capacitance | 560 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 25 VDC, 28.7 VDC (Surge) |
| Temperature Range | -55/+125°C |
| Rated Temperature | 125°C |
| Life | 2000 Hrs |
| ESR | 17 mOhms (100kHz 20C) |
| Ripple Current | 2500 mAmps (100kHz 125C) |
| Leakage Current | 2800 uA (2min 20°C) |
| High Temperature Solder | Yes |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2024 KEMET