


KEMET Part Number: ALC80A271EB450
(A547HD271M450A)

ALC80, Aluminum Electrolytic, 270 uF, 20%, 450 VDC, -40/+105°C



Dimensions

Dimension	Value
D	40mm +1mm
L	30mm +/-2mm
S	10mm +/-0.1mm
LL	6.3mm +/-1mm
F	2mm +/-0.1mm

Packaging Specifications

Weight:	55 g
Packaging:	Bulk, Bag

General Information

Supplier:	KEMET
Series:	ALC80
Dielectric:	Aluminum Electrolytic
Description:	Snap-In, Aluminum Electrolytic
RoHS:	Yes
Lead:	2 Pin
Shelf Life:	156 Weeks

Specifications

Capacitance:	270 uF
Capacitance Tolerance:	20%
Voltage DC:	450 VDC, 495 VDC (Surge)
Temperature Range:	-40/+105°C
Rated Temperature:	105°C
Life:	9000 Hrs (Rated Voltage And Ripple Current At 105C), 14000 Hrs (Rated Voltage at 105C)
Resistance:	496 mOhms (100Hz 20C), 288 mOhms (10kHz 20C)
Ripple Current:	1.96 Amps (100Hz 105C), 4.99 Amps (10kHz 105C)
Leakage Current:	364.5 uA (5min 20°C)