


**KEMET Part Number: ALC80A561EF450**  
(A547HH561M450A)

ALC80, Aluminum Electrolytic, 560 uF, 20%, 450 VDC, -40/+105°C



**Dimensions**

Dimension	Value
D	40mm +1mm
L	50mm +/-2mm
S	10mm +/-0.1mm
LL	6.3mm +/-1mm
F	2mm +/-0.1mm

**Packaging Specifications**

<b>Weight:</b>	105 g
<b>Packaging:</b>	Bulk, Bag

**General Information**

<b>Supplier:</b>	KEMET
<b>Series:</b>	ALC80
<b>Dielectric:</b>	Aluminum Electrolytic
<b>Description:</b>	Snap-In, Aluminum Electrolytic
<b>RoHS:</b>	Yes
<b>Lead:</b>	2 Pin
<b>Shelf Life:</b>	156 Weeks

**Specifications**

<b>Capacitance:</b>	560 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	450 VDC, 495 VDC (Surge)
<b>Temperature Range:</b>	-40/+105°C
<b>Rated Temperature:</b>	105°C
<b>Life:</b>	9000 Hrs (Rated Voltage And Ripple Current At 105C), 14000 Hrs (Rated Voltage at 105C)
<b>Resistance:</b>	240 mOhms (100Hz 20C), 140 mOhms (10kHz 20C)
<b>Ripple Current:</b>	3.2 Amps (100Hz 105C), 7.97 Amps (10kHz 105C)
<b>Leakage Current:</b>	756 uA (5min 20°C)