

Ident-No: ARALDITE 2012 HARDENER/HAERTER/DURCISSEUR

Version 4
Revision Date 31.01.2004

Print Date 28.02.2004

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product information

Trade name : ARALDITE 2012 HARDENER/HAERTER/DURCISSEUR

Use : Hardener for adhesive systems

Company : Huntsman Advanced Materials (Europe)BVBA
Everslaan 45
3078 Everberg / Belgium

Telephone : +41619661599
Telefax : +41619661589
Emergency telephone number : +41 61 966 40 00 (in France ORFILA : +33(0)145425959)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Formulated polyamine preparation

Hazardous components

Chemical Name	CAS-No.	Symbol(s):	R-phrase(s)	Concentration [%]
N(3-dimethylaminopropyl)-1,3-propylenediamine EC-No.: 234-148-4	10563-29-8	C	R21/22 R34 R43	1.00 - 6.00
triethylene glycol dimercaptan EC-No.: 239-044-2	14970-87-7	Xn	R20/22	1.00 - 6.00
4-dimethylaminoethyl-1-methyl-4-piperazine EC-No.: 203-183-7	104-19-8	T	R22 R24 R34	< 3.00

3. HAZARDS IDENTIFICATION

Irritating to eyes and skin.
May cause sensitization by skin contact.

4. FIRST AID MEASURES

Inhalation : Move to fresh air.
Call a physician immediately.

Eye contact : Rinse immediately with plenty of water for at least 15 minutes.
If eye irritation persists, consult a specialist.

Skin contact : Wash off with soap and plenty of water.
If skin irritation persists, call a physician.

Ingestion : Do not induce vomiting.
Immediately give plenty of water (if possible charcoal slurry).
Obtain medical attention.

Ident-No: ARALDITE 2012 HARDENER/HAERTER/DURCISSEUR

Version 4
Revision Date 31.01.2004

Print Date 28.02.2004

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray.
Dry powder.
Carbon dioxide (CO₂).
Foam.
- Extinguishing media which must not be used for safety reasons : High volume water jet.
- Specific hazards during fire fighting : Burning produces obnoxious and toxic fumes.
Carbon oxides.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Do not breathe vapours/dust.
Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation.
- Environmental precautions : Do not allow material to contaminate ground water system.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

7. HANDLING AND STORAGE

Handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Handle and open container with care.

Storage

- Further information on storage conditions : Keep away from food, drink and animal feeding stuffs.
Keep container tightly closed.
Keep at temperatures between 2 and 40°C.
- Storage hazard class : Storage class 12, Liquids, not dangerous
- Huntsman Advanced Materials

Ident-No: ARALDITE 2012 HARDENER/HAERTER/DURCISSEUR

Version 4
Revision Date 31.01.2004

Print Date 28.02.2004

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Control parameters	Update	Basis
------------	---------	--------------------	--------	-------

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Respiratory protection : In the case of hazardous fumes, wear self contained breathing apparatus.

Eye protection : goggles

Hand protection : rubber or plastic gloves

Skin and body protection : long sleeved clothing

Hygiene measures : Keep away from food, drink and animal feeding stuffs.
Wash hands before breaks and immediately after handling the product.

Protective measures : Avoid contact with skin, eyes and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : viscous

Form : liquid

Colour : yellow

Thermal decomposition : > 200 °C

Flash point : > 100 °C
Method: estimated

Vapour pressure : < 1 Pa
at 20 °C

Density : 1.15 - 1.18 g/cm³
at 25 °C

Water solubility : at 20 °C
Note: practically insoluble

Miscibility with water : immiscible
at 20 °C

Viscosity, dynamic : 20 - 40 Pa.s
at 25 °C

Ident-No: ARALDITE 2012 HARDENER/HAERTER/DURCISSEUR

Version 4
Revision Date 31.01.2004

Print Date 28.02.2004

10. STABILITY AND REACTIVITY

- Conditions to avoid : Note: Take necessary action to avoid static electricity discharge.
- Materials to avoid : Strong acids and strong bases.
Strong oxidizing agents.
- Hazardous decomposition products : Carbon oxides. Burning produces obnoxious and toxic fumes.

11. TOXICOLOGICAL INFORMATION

- Acute oral toxicity : LD50 rat
Dose: 2,300 mg/kg
- Eye irritation : irritating
rabbit
- Skin irritation : Moderate skin irritation
rabbit
dermal
- Sensitization : Causes sensitization on guinea-pigs.
guinea pig

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

- Biodegradability : Result: Not readily biodegradable.

Ecotoxicity effects

Further information on ecology

- Additional ecological information : Avoid subsoil penetration.
Prevent product from entering drains.
Do not contaminate surface water.

13. DISPOSAL CONSIDERATIONS

- Product : Waste Key Number: 070204
Must be incinerated, when in compliance with local regulations.
- Container : Empty containers can be landfilled after cleaning, when in compliance with the Environmental Protection (Duty of Care) Regulations 1991.

Ident-No: ARALDITE 2012 HARDENER/HAERTER/DURCISSEUR

Version 4
Revision Date 31.01.2004

Print Date 28.02.2004

14. TRANSPORT INFORMATION

Land transport

ADR:

Regulation: Not dangerous goods

RID:

Regulation: Not dangerous goods

Sea transport

IMDG:

Regulation: Not dangerous goods

Air transport

IATA-DGR:

Regulation: Not dangerous goods

15. REGULATORY INFORMATION

Labelling according to EEC Directive

Labelling required

Symbol(s):	: Xi	Irritant
R-phrase(s)	: R36/38 R43	Irritating to eyes and skin. May cause sensitization by skin contact.
S-phrase(s)	: S26 S28 S37/39	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water. Wear suitable gloves and eye/face protection.
Hazardous components which must be listed on the label	: N(3-dimethylaminopropyl)-1,3-propylenediamine EC-No.: 234-148-4 4-dimethylaminoethyl-1-methyl-4-piperazine EC-No.: 203-183-7	

National legislation

Ident-No: ARALDITE 2012 HARDENER/HAERTER/DURCISSEUR

Version 4
Revision Date 31.01.2004

Print Date 28.02.2004

Notification status

- : EINECS yes
- : TSCA no
- : DSL no
- : AICS no
- : KECI (KR) no
- : JEX (JP) no

16. OTHER INFORMATION

List of R-phrases (Section 2)

- | | |
|--------|--|
| R20/22 | Harmful by inhalation and if swallowed. |
| R21/22 | Harmful in contact with skin and if swallowed. |
| R22 | Harmful if swallowed. |
| R24 | Toxic in contact with skin. |
| R34 | Causes burns. |
| R43 | May cause sensitization by skin contact. |

The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974. Users of products supplied by Huntsman Advanced Materials should take appropriate measures to ensure working practices are in accordance with the Control of Substances Hazardous to Health Regulations (COSHH).

All information is based on results gained from experience and tests and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry out sufficient tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressly agreed in writing nor construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Huntsman Advanced Materials General Conditions of Sale.

Ident-No: ARALDITE 2012 RESIN(E)/HARZ

Version 5
Revision Date 31.01.2004

Print Date 28.02.2004

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product information

Trade name : ARALDITE 2012 RESIN(E)/HARZ

Use : Resin for adhesive systems

Company : Huntsman Advanced Materials (Europe)BVBA
Everslaan 45
3078 Everberg / Belgium

Telephone : +41619661599
Telefax : +41619661589
Emergency telephone number : +41 61 966 40 00 (in France ORFILA : +33(0)145425959)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Bisphenol A epoxy resin containing reactive diluent preparation

Hazardous components

Chemical Name	CAS-No.	Symbol(s):	R-phrases	Concentration [%]
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight < 700)	25068-38-6	Xi, N	R36/38 R43 R51/53	80.00 - 92.00
butanedioldiglycidyl ether EC-No.: 219-371-7	2425-79-8	Xn	R20/21 R36/38 R43 R52/53	3.00 - 9.00

3. HAZARDS IDENTIFICATION

Irritating to eyes and skin.
May cause sensitization by skin contact.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES

Inhalation : Move to fresh air.
Call a physician immediately.

Eye contact : Rinse immediately with plenty of water for at least 15 minutes.
If eye irritation persists, consult a specialist.

Skin contact : Wash off with soap and plenty of water.
If skin irritation persists, call a physician.

Ingestion : Do not induce vomiting.
Immediately give plenty of water (if possible charcoal slurry).
Obtain medical attention.

Ident-No: ARALDITE 2012 RESIN(E)/HARZ

Version 5
Revision Date 31.01.2004

Print Date 28.02.2004

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray.
Dry powder.
Carbon dioxide (CO₂).
Foam.
- Extinguishing media which must not be used for safety reasons : High volume water jet.
- Specific hazards during fire fighting : Burning produces obnoxious and toxic fumes.
Carbon oxides.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Do not breathe vapours/dust.
Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation.
- Environmental precautions : Do not allow material to contaminate ground water system.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

7. HANDLING AND STORAGE

Handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Handle and open container with care.

Storage

- Further information on storage conditions : Keep away from food, drink and animal feeding stuffs.
Keep container tightly closed.
Keep at temperatures between 2 and 40°C.
- Storage hazard class : Storage class 10, Environmentally hazardous liquids
Huntsman Advanced
Materials

Ident-No: ARALDITE 2012 RESIN(E)/HARZ

Version 5
Revision Date 31.01.2004

Print Date 28.02.2004

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Control parameters	Update	Basis
------------	---------	--------------------	--------	-------

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Respiratory protection : In the case of hazardous fumes, wear self contained breathing apparatus.
- Eye protection : goggles
- Hand protection : rubber or plastic gloves
- Skin and body protection : long sleeved clothing
Remove and wash contaminated clothing before re-use.
- Hygiene measures : Keep away from food, drink and animal feeding stuffs.
Wash hands before breaks and immediately after handling the product.
- Protective measures : Avoid contact with skin, eyes and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : liquid
- Colour : light yellow
- Odour : slight
- pH : 6
at (20 °C)
1:1 in water
- Thermal decomposition : > 200 °C
- Flash point : > 200 °C
Method: DIN 51758 (Pensky-Martens Closed Cup)
- Density : 1.17 g/cm³
at 25 °C
- Water solubility : at 20 °C
Note: practically insoluble
- Miscibility with water : immiscible
at 20 °C

Ident-No: ARALDITE 2012 RESIN(E)/HARZ

Version 5
Revision Date 31.01.2004

Print Date 28.02.2004

Viscosity, dynamic : 25 - 45 Pa.s
at 25 °C

10. STABILITY AND REACTIVITY

Conditions to avoid : Note: Take necessary action to avoid static electricity discharge.

Materials to avoid : Strong acids and strong bases.
Strong oxidizing agents.

Hazardous decomposition products : Carbon oxides. Burning produces obnoxious and toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50 rat
Dose: > 5,000 mg/kg

Eye irritation : irritating
rabbit

Skin irritation : irritating
rabbit
dermal

Sensitization : Causes sensitization.
guinea pig
dermal

Further information : Epoxy resins with an average molecular weight of less than 700 may cause sensitization.

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

Biodegradability : Result: Not readily biodegradable.

Ecotoxicity effects

Further information on ecology

Additional ecological information : Avoid subsoil penetration.
Prevent product from entering drains.
Do not contaminate surface water.

13. DISPOSAL CONSIDERATIONS

Product : Waste Key Number: 070208
Must be incinerated, when in compliance with local regulations.

Ident-No: ARALDITE 2012 RESIN(E)/HARZ

Version 5
Revision Date 31.01.2004

Print Date 28.02.2004

Container : Empty containers can be landfilled after cleaning, when in compliance with the Environmental Protection (Duty of Care) Regulations 1991.

14. TRANSPORT INFORMATION

Land transport

ADR:

UN-No: 3082
Class: 9
Classification code: M6
Packaging group: III
Risk No.: 90
ADR/RID-Labels: 9
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
contains: BISPHENOL A EPOXY RESIN

RID:

UN-No: 3082
Class: 9
Packaging group: III
Risk No.: 90
ADR/RID-Labels: 9
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
contains: BISPHENOL A EPOXY RESIN

Sea transport

IMDG:

UN-No: 3082
Class: 9
Packaging group: III
ADR/RID-Labels: 9
MFAG:
EmS: F-A S-F
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
contains: (BISPHENOL A EPOXY RESIN)

Air transport

IATA-DGR:

UN/ID No.: UN 3082
Class: 9
Packaging group: III
Packing instruction (cargo aircraft): 914

Ident-No: ARALDITE 2012 RESIN(E)/HARZ

Version 5
Revision Date 31.01.2004

Print Date 28.02.2004

Max. Qty/Pack.: 999.00 L
(999.00 = No limit)
Packing instruction 914
(passenger aircraft):
Max. Qty/Pack.: 999.00 L
(999.00 = No limit)
ADR/RID-Labels: 9
Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
contains: (BISPHENOL A EPOXY RESIN)

15. REGULATORY INFORMATION

Labelling according to EEC Directive

Labelling required

Symbol(s): : Xi Irritant
N Dangerous for the environment

R-phrase(s) : R36/38 Irritating to eyes and skin.
R43 May cause sensitization by skin contact.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrase(s) : S28 After contact with skin, wash immediately with plenty of soap and water.
S37/39 Wear suitable gloves and eye/face protection.
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Exceptional labelling of special preparations : Contains epoxy constituents. See information supplied by the manufacturer.

Hazardous components which must be listed on the label : butanedioldiglycidyl ether
EC-No.: 219-371-7
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight < 700)

National legislation

Notification status

: EINECS yes

Ident-No: ARALDITE 2012 RESIN(E)/HARZ

Version 5
Revision Date 31.01.2004

Print Date 28.02.2004

- : TSCA yes
- : DSL yes
- : AICS yes
- : KECI (KR) yes
- : JEX (JP) yes

16. OTHER INFORMATION

List of R-phrases (Section 2)

R20/21	Harmful by inhalation and in contact with skin.
R36/38	Irritating to eyes and skin.
R43	May cause sensitization by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974. Users of products supplied by Huntsman Advanced Materials should take appropriate measures to ensure working practices are in accordance with the Control of Substances Hazardous to Health Regulations (COSHH).

All information is based on results gained from experience and tests and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry out sufficient tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressly agreed in writing nor construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Huntsman Advanced Materials General Conditions of Sale.