



Blackburn®

Dual-Rated
T&B Catalog Number:

ASL60-22
78378613315
Active

UPC Number:
Status:
Description:

Type ASL-ALCUL Two-Conductor, Two-Hole Mount for Conductor Range
Max 600 kcmil, Min 2 Str.

Features

Easy Installation - no special tools required.

General

Style	ALCUL Two-Conductor, Two-Hole Mount
Material	Aluminum
Plating	Tin-Plated
Conductor Range (AL or CU) Maximum	600 kcmil
Conductor Range (AL or CU) Minimum	2 Str.

Dimension Information

Length (inches)	4 29/32
Width (inches)	1 1/2
Height (inches)	3
D (inches)	3/4
F (inches)	3/8

Packaging

T&B Order Multiple	3
T&B Inner Pack	3
Package in Units	30
T&B Sold in UOM	Each
T&B Weight Per UOM	0.72 lbs. Each

Application Support

T&B Sales Drawings	wsd-000463
--------------------	------------

Notes

UL 486B tested, AL9CU rated

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com

