







<table border="1"> <tr> <td>8P</td> <td>TPU</td> <td>5.8</td> <td>24</td> <td>ASU-08BFFM-QL8BXX</td> <td>REV.</td> <td>ECN NO.</td> <td>DATE</td> <td>SIGN</td> <td>DESCRIPTION</td> </tr> <tr> <td>Contacts</td> <td>Cable Jacket</td> <td>Cable OD</td> <td>AWG</td> <td>Item No.</td> <td>A</td> <td></td> <td>2022-02-23</td> <td>Jiahe Lin</td> <td>Rev.01 to A, Initial Released</td> </tr> </table>	8P	TPU	5.8	24	ASU-08BFFM-QL8BXX	REV.	ECN NO.	DATE	SIGN	DESCRIPTION	Contacts	Cable Jacket	Cable OD	AWG	Item No.	A		2022-02-23	Jiahe Lin	Rev.01 to A, Initial Released	<table border="1"> <tr> <td>TITLE</td> <td>XLOK, A SHLD-2A, 08P, CABLE W/O SR</td> <td>DATE</td> <td>2022-02-23</td> </tr> <tr> <td>SCALE</td> <td>2:1</td> <td>SHEET</td> <td>1 OF 1</td> </tr> <tr> <td>REV.</td> <td>A</td> <td>AW-REV.</td> <td></td> </tr> </table>	TITLE	XLOK, A SHLD-2A, 08P, CABLE W/O SR	DATE	2022-02-23	SCALE	2:1	SHEET	1 OF 1	REV.	A	AW-REV.		<p>UNIT: mm</p> <p>TOLERANCE</p> <p>±0.5mm</p>		<p>DRWN BY</p> <p>Jiahe Lin</p>	<p>DATE</p> <p>2022-02-23</p>	<p>CHECKED BY</p> <p>Allen Pan</p>	<p>DATE</p> <p>2022-02-23</p>	<p>APPROVED BY</p> <p>Fred Lee</p>	<p>DATE</p> <p>2022-02-23</p>
8P	TPU	5.8	24	ASU-08BFFM-QL8BXX	REV.	ECN NO.	DATE	SIGN	DESCRIPTION																																
Contacts	Cable Jacket	Cable OD	AWG	Item No.	A		2022-02-23	Jiahe Lin	Rev.01 to A, Initial Released																																
TITLE	XLOK, A SHLD-2A, 08P, CABLE W/O SR	DATE	2022-02-23																																						
SCALE	2:1	SHEET	1 OF 1																																						
REV.	A	AW-REV.																																							
<p>Shield Braid</p> <p>8 Red</p> <p>7 Blue</p> <p>6 Pink</p> <p>5 Gray</p> <p>4 Yellow</p> <p>3 Green</p> <p>2 Brown</p> <p>1 White</p>	<p>編織</p> <p>紅</p> <p>藍</p> <p>粉紅</p> <p>灰</p> <p>黃</p> <p>綠</p> <p>棕</p> <p>白</p>	<p>Pin # Wire</p>	 <p>8P</p> <p>Pin Assignments Front View</p>				<p>ASU-XXBFFM-QL8BXX</p> <p>XX: L=0~99Meters</p> <p>01: L=1Meters</p> <p>02: L=2Meters</p> <p>...</p> <p>99: L=99Meters</p> <p>XX: No. Of Pin</p>	<p>Note:</p> <ul style="list-style-type: none"> * RoHS Compliant *  Important dimension * Waterproof rate: IPX8, mated 1m/24h * Connector 	<p>Housing: Thermoplastic, Black</p> <p>Pin: Copper alloy, Gold plated</p> <p>Shield: Metal</p> <p>Nut: Metal</p> <p>Outer mold: Thermoplastic, Black</p> <p>* Cable: UL20549, TPU Jacket, Black</p> <p>* Cable length tolerance:</p> <p>1M: +50/-0 mm</p> <p>1M < L ≤ 3M: +100/-0 mm</p> <p>3M < L ≤ 5M: +150/-0 mm</p> <p>5M < L ≤ 10M: ±100 mm</p> <p>10M < L ≤ 20M: ±200 mm</p> <p>20M < L ≤ 30M: ±300 mm</p> <p>30M < L ≤ 99M: ±500 mm</p>	<p>Amphenol LTW</p> <p>安費諾亮泰企業股份有限公司</p>	<p>ITEM NO</p> <p>ASU-XXBFFM-QL8BXX</p> <p>CUSTOMER</p> <p>ALTW</p>	<p>DATE</p> <p>2022-02-23</p>	<p>DATE</p> <p>2022-02-23</p>	<p>DATE</p> <p>2022-02-23</p>	<p>8</p> <p>WIDB14-03-PM01A2</p>																										