REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1	-	RELEASED DRAWING	FEB-14-19	WHITE	TOMMY
A2	-	UPDATE DRAWING	JAN-16-20	BLINK	TOMMY













NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:
   HOUSING: THERMOPLASTIC; COLOR:BLACK
   SEAL: SILICONE RUBBER

2. MODIFICAIONS: N/A

3. SPECIFICATIONS:
   3.1 CURRENT RATING: 100 AMPS
   3.2 VOLTAGE RATING: 1000 V AC/DC
   3.3 OPERATING TEMPERATURE: -55°C TO +125°C
   3.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 3000 VOLTS AC.
   3.5 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
   3.6 MOISTURE RESISTANCE: IP67 AND IP69K (MATED CONDITION)
   3.7 MATING CYCLE DURABILITY: 100 CYCLES
   3.8 RoHS COMPLIANT

4. MATING PART:ATHD06-1-4S* PLUG
   (* = MODIFICATIONS)

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

△6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE
04	6.63 mm (.261 in)	10.67 mm (.420 in)	4 - 6 AWG (21-13 mm²)

	ATHD04-1-4P		
	PART NUMBER	DESCRIPTION	ITEM
QUANTITY	MATERIALS LIST		

UNLESS OTHERWISE SPECIFIED
1) All dimensions are in metric(mm).
2) Tolerances are as follows:
1 PL DEC ±0.30 | Fractions ±1/64
2 PL DEC ±0.15 | Angles ±1°
3 PL DEC ±0.08
3) Note reference = △X

MATERIAL SPECIFICATIONS:

PROCESS SPECIFICATIONS:

NEXT ASSY:

SIGNATURES		DATE
DRAWN:	BLINK	JAN-16-20
CHECKED:	ORION	JAN-16-20
ENGINEER:		
APPROVAL:	TOMMY	JAN-16-20
CUSTOMER:		

THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.

Amphenol
Sine Systems - www.amphenol-sine.com
44724 Morley Drive
Clinton Township, MI 48036

RECEPTACLE,1 WAY,SIZE 4,ATHD SERIES

SIZE	TYPE	DWG NO:	REVISION
B	C-	ATHD04-1-4P	A2

SCALE: NONE SHEET 1 OF 1

TITLE: RECEPTACLE,1 WAY,SIZE 4,ATHD SERIES
DWG NO: ATHD04-1-4P
REV: A2
SH: 1
OF: 1