



NOTES
 1 - NICKEL PLATE, BRIGHT, 0,005-0,010 THICK
 2 - MATERIAL TEMPER: ANNEALED

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:	<input type="checkbox"/>	US (inch)	<input checked="" type="checkbox"/>	SI (mm)
		CUSTOMARY		METRIC
NO PLACE	(X)	±.040	±1	
ONE PLACE	(.X)	±.030	±0,4	
TWO PLACE	(.XX)	±.015	±0,15	
THREE PLACE	(.XXX)	±.005	±	
ANGLES		±	±	
RAW MATERIAL—COMMERCIAL STANDARD				
MICRO SWITCH STANDARDS APPLY				

DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL'S MICRO SWITCH DIVISION. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF HONEYWELL.

REV LET	REVISION	REVISION NOTICE	CHANGED BY	CHECKED BY
A	REV INSP, NOTE & MAT'L	90010	J A K JUN 96	

TITLE POLE PIECE
 REPLACES SKETCH07497A
 RELEASING DOCUMENT DR-4200

MATERIAL—PLAIN CARBON AND ALUMINUM KILLED COLD ROLLED STEEL / 09-54489

CAD	DRAWN	J A K	17 JUN 96	Honeywell	THIRD ANGLE PROJECTION 	SCALE 3 : 1	DRAWING NUMBER AV-10379
DDM	D'FT'G CHECK						