

AZ733W

DPST MINIATURE POWER RELAY

FEATURES

- Dielectric strength 5000 Vrms
- 1.5 mm contact gap (2.0mm contact gap available)
- Epoxy sealed version available
- 10 Amp switching — double pole contacts
- Isolation spacing greater than 8 mm
- UL Class B insulation system, Class F available-
- UL, CUR file E44211
- TÜV file R50129285



CONTACTS

Arrangement	DPST (2 Form A)
Ratings	Resistive load: Max. switched power: 300 W or 2500 VA Max. switched current: 10 A Max. switched voltage: 150 VDC* or 400 VAC *Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Rated Load UL, CUR TÜV	10 A at 250 VAC General use, 100k cycles [1][2][3] TV-3 at 125 VAC [1] 10 A at 30 VDC, 250 VAC resistive, 100k cycles [1] [2][3] [1] Silver cadmium oxide [2] Silver tin oxide [3] Silver nickel
Material	Silver cadmium oxide, silver tin oxide or silver nickel, Gold plating available
Resistance	< 50 milliohms initially (24 V, 1 A voltage drop method)

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 5 x 10 ⁵ 1 x 10 ⁵ at 10 A 240 VAC Res.
Operate Time (Typical)	10 ms at nominal coil voltage
Release Time (Typical)	4 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	5000 Vrms contact to coil 2500 Vrms between open contacts 3000 Vrms between contact sets
Insulation Resistance	1000 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	at nominal coil voltage -40°C (-40°F) to 80°C (176°F) -40°C (-40°F) to 130°C (266°F)
Vibration	0.062" DA at 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	18 grams

COIL

Power At Pickup Voltage (typical) Max. Continuous Dissipation Temperature Rise	450 mW 2.0 W at 20°C (68°F) ambient 40°C (83°F) at nominal coil voltage
Temperature	Max. 130°C (266°F) Class B Max. 155°C (311°F) Class F

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

AZ733W

RELAY ORDERING DATA

COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance	Unsealed	Sealed
3	2.25	4.7	11.3 ±10%	AZ733W-2A-3D	AZ733W-2A-3DE
5	3.8	7.9	31 ±10%	AZ733W-2A-5D	AZ733W-2A-5DE
6	4.5	9.5	45 ±10%	AZ733W-2A-6D	AZ733W-2A-6DE
9	6.8	14.2	101 ±10%	AZ733W-2A-9D	AZ733W-2A-9DE
12	9.0	18.9	180 ±10%	AZ733W-2A-12D	AZ733W-2A-12DE
18	13.5	28.4	405 ±10%	AZ733W-2A-18D	AZ733W-2A-18DE
24	18.0	37.9	720 ±15%	AZ733W-2A-24D	AZ733W-2A-24DE
30	22.5	47.3	1125 ± 15%	AZ733W-2A-30D	AZ733W-2A-30DE
48	36.0	75.9	2,880 ±15%	AZ733W-2A-48D	AZ733W-2A-48DE
60	45.0	94.8	4,500 ±15%	AZ733W-2A-60D	AZ733W-2A-60DE

*Add suffix "E" to "2A" for silver tin oxide contacts. Add suffix "B" to "2A" for silver nickel contacts. Add suffix "F" for Class F insulation system. Add suffix "A" for gold plated contacts. When suffix "E" is specified for Epoxy Seal, refer to AZ "Relay Technical Notes" on AZ website - Product Resources. Consult factory for other PCB process conditions that may apply.

HARDWARE ORDERING DATA

DESCRIPTION	ORDER NUMBER	DESCRIPTION	ORDER NUMBER
Socket	ST484-U1	Retainer	ST482-2

MECHANICAL DATA

Terminal No.	Dimensions Tol.: ± 0.005 (0.13)
1,4,5,8	0.018 (0.457) x 0.038 (0.965)
3,6	0.011 (0.279) x 0.038 (0.965)

PC BOARD LAYOUT (Bottom View)

WIRING DIAGRAM (Bottom View)

ST484-U1 HARDWARE

Viewed toward terminals

RETAINING CLIP ST482-2

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± .010"



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM