


AZ942H

16 AMP MINIATURE PC BOARD RELAY



FEATURES

- Extremely low cost
- 16 Amp switching capacity
- Proof tracking index (PTI/CTI) 250
- Clearance and creepage distance >2.5 mm
- Class F insulation (155 °C) available
- Meets IEEE 587 6 kV lightning surge
- UL, CUR file E43203
- VDE file 40026048

CONTACTS

Arrangement	SPST (1 Form A) SPDT (1 Form C)
Ratings	Resistive load:
1 Form A	Max. switched power: 280 W or 4000 VA Max. switched current: 16 A Max. switched voltage: 150 VDC* or 300 VAC
1 Form C	Max. switched power: 196 W or 1939 VA Max. switched current: 12 A Max. switched voltage: 150 VDC* or 300 VAC
	* Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Rated Load UL	1 Form A 16 A at 250 VAC, resistive, 85°C, 50k cycles [2] 12 A at 250 VAC, resistive, 85°C, 100k cycles [2] 10 A at 277 VAC, resistive, 85°C, 25k cycles [2], [1] 10 A at 28 VDC, resistive, 85°C, 100k cycles [2], [1] 1/2 HP at 125 / 250 VAC 1 Form C 16 A at 250 VAC, resistive, 85°C, 50k cycles (N.O.) [2] 12 A at 250 VAC, resistive, 85°C, 100k cycles (N.O.) [2] 12 A at 125 VAC, resistive, 85°C, 100k cycles (N.O.) [2], [1] 12 A at 125 VAC, resistive, 85°C, 100k cycles (N.C.) [2] 7 A at 277 VAC, resistive, 85°C, 100k cycles [2], [1] 7 A at 28 VDC, resistive, 85°C, 100k cycles [2], [1] 1/2 HP at 125 / 250 VAC 4 FLA / 4 LRA at 240 VAC (N.O.) [2] 2 FLA / 4 LRA at 240 VAC (N.C.) [2]
VDE	1 Form A 10 A at 250 VAC, resistive, 85°C, 50k cycles [2] 1 Form C 10 A at 250 VAC, resistive, 85°C, 50k cycles (N.O.) [2] 7 A at 250 VAC, resistive, 85°C, 50k cycles [2]
Material	Silver cadmium oxide [1] or Silver tin oxide [2]
Resistance	< 100 milliohms initially

NOTES

1. All values at 20°C (68°F)
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁷ 1 x 10 ⁵ at 10A 250 VAC Res.
Operate Time (typical)	10 ms at nominal coil voltage
Release Time (typical)	5 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	3000 Vrms contact to coil 1000 Vrms across contacts
Insulation Resistance	100 megohms min. at 20°C, 500 VDC, 50% RH
Insulation (according to DIN VDE 0110, IEC 60664-1)	Overvoltage category: II Pollution degree: 2 Nominal voltage: 250 VAC
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage Class B: -40°C(-40°F) to 70°C(158°F) Class F: -40°C(-40°F) to 85°C(185°F) -40°C(-40°F) to 105°C(221°F)
Vibration	0.062" (1.5 mm) DA at 10–55Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	13 g
Packing unit in pcs	20 per plastic tube / 1000 per carton box

COIL

Power At Pickup Voltage (typical)	230 mW
Max. Continuous Dissipation	Class B: 1.7 W at 20°C (68°F) ambient Class F: 2.2 W at 20°C (68°F) ambient
Temperature Rise	26°C (47°F) at nominal coil voltage
Temperature	Class B: Max. 130°C (221°F) Class F: Max. 155°C (311°F)



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

AZ942H

RELAY ORDERING DATA

STANDARD RELAYS				ORDER NUMBER*	
COIL SPECIFICATIONS				Form A (SPST-N.O.)	Form C (SPDT)
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance Ohm $\pm 10\%$		
3	2.4	6.5	25	AZ942H-1A-3D	AZ942H-1C-3D
5	4.0	11.0	70	AZ942H-1A-5D	AZ942H-1C-5D
6	4.8	13.0	100	AZ942H-1A-6D	AZ942H-1C-6D
9	7.2	20.0	225	AZ942H-1A-9D	AZ942H-1C-9D
12	9.6	26.0	400	AZ942H-1A-12D	AZ942H-1C-12D
18	14.4	39.0	900	AZ942H-1A-18D	AZ942H-1C-18D
24	19.2	52.0	1,600	AZ942H-1A-24D	AZ942H-1C-24D
48	38.4	104.0	6,200	AZ942H-1A-48D	AZ942H-1C-48D

* For epoxy sealed version, add suffix "E." For silver tin oxide contacts add suffix "T." To indicate Class F version, add suffix "F."

IEEE STANDARD 587-1980 (ANSI/IEEE C62.41-1980) SURGE VOLTAGE WITHSTAND RATING

Test	Rating	Description
1.2 x 50 usec positive pulse	6 kV	Contact to coil - 5 pulses
1.2 X 50 usec negative pulse	6 kV	Contact to coil - 5 pulses
0.5 us 100 kHz ring wave	6 kV	Contact to coil - 5 waves

MECHANICAL DATA

Top view dimensions: .87 [22.0] (width), .65 [16.5] (height), .64 [16.3] (width), .138 [3.5] (height), .016 [0.4] (height).

Bottom view dimensions: .016 [0.4] (height), .040 [1.0] (height), 4 x .020 [0.5] (width), 4 x .036 [0.9] (width).

PC BOARD LAYOUT

Dimensions: .082 [2.1] (width), .085 [2.15] (width), .472 [12.0] (height), .236 [6.0] (height), .078 [2.0] (width), .480 [12.2] (width), 5 x \varnothing .051 [\varnothing 1.3] (terminals).

VIEWED TOWARDS TERMINALS

WIRING DIAGRAMS

FORM A

FORM C

VIEWED TOWARDS TERMINALS

Dimensions in inches with metric equivalents in parentheses. Tolerance: ± 0.010 "



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM