

**Basic features**

Approval/Conformity	CE
	EAC
	WEEE

**Electrical connection**

Bending radius min., fixed cable	5 x D
Bending radius min., flexible cable	10 x D
Cable	PUR black, 2.00 m, Drag chain compatible
Cable diameter D	4.60 mm ±0.20 mm
Cable, bending cycles min.	2 million
Conductor cross-section	0.50 mm <sup>2</sup>
Connection	B, Ind.-180°-Valve connector, right-angle, 3-pin
Connector configuration	right-angle
Number of conductors	3
Number of pins	3
System	Molded

**Electrical data**

Operating voltage U <sub>b</sub>	230 VDC / 230 VAC
Rated current (40 °C)	4.0 A

**Environmental conditions**

Cable temperature, drag chain	-25...60 °C
Cable temperature, fixed routing	-50...80 °C
Cable temperature, flexible routing	-25...80 °C
Protection degree	IP67

**Material**

Cable jacket, material	PUR
Material contact carrier	PBT
Material contacts	Brass
Material grip	TPU
Material locking screw	Steel

Single-Ended Cordsets  
**BCC VB63-0000-10-056-PX0350-020**  
Order Code: BCC03Z5



**Mechanical data**


Acceleration max., drag chain	5 m/s <sup>2</sup>
Cable jacket, color	black
Cable length L	2.00 m
Cable properties	Drag chain compatible

Horizontal travel permitted, drag chain	5 m
Tightening torque pigtail	0.5 Nm
Traverse speed max., drag chain	200 m/min
Vertical travel permitted, drag chain	2 m

**Remarks**

Cable construction acc. to UL-AWM Style 20549  
Halogen-free acc. to EN 50267-2-1  
Silicone-free  
Flame resistance per IEC 60332-2-2  
\* style B industry standard  
Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

**Connector Drawings**



PIN 1: brown  
PIN 2: blue  
PIN PE: green/yellow

**Wiring Diagrams**

