

Product designation				Power contactor
Product type designation				BF18
Contact characteristics				
Number of poles		Nr.	4	
Rated insulation voltage U _i IEC/EN		V	690	
Rated impulse withstand voltage U _{imp}		kV	6	
Operational frequency		min	Hz	25
		max	Hz	400
IEC Conventional free air thermal current I _{th}		A	32	
Operational current I _e		AC-1 (≤40°C)	A	32
		AC-1 (≤55°C)	A	26
		AC-1 (≤70°C)	A	23
		AC-3 (≤440V ≤55°C)	A	18
		AC-4 (400V)	A	8.5
Rated operational power AC-1 (T≤40°C)		230V	kW	12
		400V	kW	21
		500V	kW	26
		690V	kW	36
Short-time allowable current for 10s (IEC/EN60947-1)		A	200	
Protection fuse		gG (IEC)	A	32
		aM (IEC)	A	20
Making capacity (RMS value)		A	180	
Breaking capacity at voltage		440V	A	144
		500V	A	120
		690V	A	94
Resistance per pole (average value)		mΩ	2.5	
Power dissipation per pole (average value)		I _{th}	W	2.6
		AC3	W	0.8
Tightening torque for terminals		min	Nm	1.5
		max	Nm	1.8
		min	lbin	1.1
		max	lbin	1.5
Tightening torque for coil terminal		min	Nm	0.8
		max	Nm	1
		min	lbin	Prodotti finiti
		max	lbin	Prodotti finiti
Max number of wires simultaneously connectable		Nr.	2	
Conductor section	Flexible w/o lug conductor section	min	mm ²	1
		max	mm ²	6
	Flexible c/w lug conductor section	min	mm ²	1
		max	mm ²	4
Flexible with insulated spade lug conductor section				

	min	mm ²	1
	max	mm ²	4
Power terminal protection according to IEC/EN 60529			IP20 when wired
Mechanical features			
Operating position	normal allowable		Vertical plan ±30°
Fixing			Screw / DIN rail 35mm
Weight		g	500
Operations			
Mechanical life		cycles	20000000
Electrical life		cycles	1600000
Safety related data			
Performance level B10d according to EN/ISO 13489-1	rated load mechanical load	cycles	1600000
		cycles	20000000
Mirror contacts according to IEC/EN 60947-4-1			YES
EMC compatibility			Yes
DC coil operating			
DC rated control voltage		V	110
DC operating voltage			
pick-up	min	%Us	70
	max	%Us	125
drop-out	min	%Us	10
	max	%Us	40
Average coil consumption ≤20°C	in-rush holding	W	5.4
		W	5.4
Max cycles frequency			
Mechanical operation		cycles/h	3600
Operating times			
Average time for Us control in AC			
	Closing NO	min	ms 8
		max	ms 24
	Opening NO	min	ms 10
		max	ms 20
	Closing NC	min	ms 14
		max	ms 28
	Opening NC	min	ms 7
		max	ms 18
	in DC		
	Closing NO	min	ms 54
		max	ms 66
	Opening NO	min	ms 14

Closing NC	max	ms	17
	min	ms	24
Opening NC	max	ms	30
	min	ms	47
	max	ms	57

UL technical data

Full-load current (FLA) for three-phase AC motor

at 480V	A	14
at 600V	A	17

Yielded mechanical performance

for single-phase AC motor

110/120V	HP	1
230V	HP	3

for three-phase AC motor

200/208V	HP	5
220/230V	HP	5
460/480V	HP	10
575/600V	HP	15

General USE

Contactor

AC current	A	32
------------	---	----

Ambient conditions

Temperature

Operating temperature

min	°C	-50
max	°C	70

Storage temperature

min	°C	-60
max	°C	80

Max altitude

m	3000
---	------

Resistance & Protection

Pollution degree

3

Dimensions

Wiring diagrams

Certifications and compliance

Compliance

CSA C22.2 n° 60947-1

CSA C22.2 n° 60947-4-1

IEC/EN 60947-1

IEC/EN 60947-4-1

UL 60947-1

UL 60947-4-1

Certificates

CCC

cULus

EAC

ETIM classification

ETIM 8.0

EC000066 -
Power contactor,
AC switching