


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
04/12/19	A	UPDATED TO "ROHS COMPLIANT"	T.B.	B.S.	
11/26/19	B	ADDED DIM. 11.40 WAS RATED 30AMP.	T.B.	B.S.	
05/13/24	C	ADDED TOTAL WIRE LENGTH	D.L.	B.S.	

NOTES:

1. MATERIAL:
HOUSING : PVC, UL 94V-0, FLEX 60GPVC, UL FILE NO. E506788
 2. LEAD WIRE IN LOOP: RED WIRE, 12AWG, UL-1015, 600V, 105°C, FLAME RATING VW-1, UL FILE NO. E250011, OR ENGINEERING APPROVED EQUIVALENT
 3. RATED CURRENT: 25A
 4. ACCEPTS ATP/ATC/ATO FUSES
 5. INSULATION RESISTANCE AT 500V DC: 100M Ω MIN
 6. CONTACT RESISTANCE: 5m Ω AT 1A DC
 7. DIELECTRIC STRENGTH FOR 60 SECONDS: AC 1000V MIN
- ROHS COMPLIANT

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735		
	decimal ±.5 (.020)	Scale	Drawn By B.S. Approved By D.L.
Fractional ± .8 (.030)	Title INLINE FUSE HOLDER		
Angular ± 3°	Date 05/13/24	Drawing Number BF351	