


## Interference Suppression Film Capacitors MKP Radial Potted Type



Dimensions in mm

**Note**

- (1)  $|F - F'| < 0.3 \text{ mm}$   
 $F = 7.5 \text{ mm} + 0.6 \text{ mm} / - 0.1 \text{ mm}$

**APPLICATIONS**

For standard across the line X1 applications.  
 See also Application Note:  
[www.vishay.com/doc?28153](http://www.vishay.com/doc?28153)

**REFERENCE STANDARDS**

"IEC 60384-14 ed-3 and EN 60384-14"  
 "IEC 60065, pass. flamm. class B"  
 UL1414; UL1283; CSA-C22.2 No. 8

**MARKING**

C-value; tolerance; rated voltage; sub-class; manufacturer's type designation; code for dielectric material; manufacturer location; manufacturer's logo; year, week and safety approvals.

**DIELECTRIC**

Polypropylene film

**ELECTRODES**

Metallized film

**CONSTRUCTION**

Mono construction


**RATED VOLTAGE**

AC 440 V; 50 Hz to 60 Hz

**FEATURES**

- 15 mm to 27.5 mm lead pitch and 15 mm bent back to 7.5 mm  
 Supplied loose in box, taped on ammpack or reel
- Compliant to RoHS Directive 2002/95/EC



**RoHS**  
COMPLIANT

**PERMISSIBLE DC VOLTAGE**

DC 1000 V

**ENCAPSULATION**

Plastic case, epoxy resin sealed, flame retardant  
 UL-class 94 V-0

**CLIMATIC TESTING CLASS ACC. TO IEC 60068-1**

55/105/56/B

**CAPACITANCE RANGE (E12 SERIES)**

E12 series 0.01  $\mu\text{F}$  to 1  $\mu\text{F}$   
 Preferred values acc. to E6

**CAPACITANCE TOLERANCE**

$\pm 20 \%$ ;  $\pm 10 \%$ ;  $\pm 5 \%$

**LEADS**

Tinned wire


**MAXIMUM APPLICATION TEMPERATURE**

105 °C

**DETAIL SPECIFICATION**

For more detailed data and test requirements contact:  
[RFI@vishay.com](mailto:RFI@vishay.com)

## COMPOSITION OF CATALOG NUMBER



TYPE	PACKAGING	LEAD CONFIGURATION	C-TOL	PREFERRED TYPES
338 1 X1	Loose in box	Lead length 3.5 mm ± 0.3 mm	± 20 %	BFC2 338 10 ...
		Lead length 5.0 mm ± 1.0 mm		BFC2 338 12 ...
		Lead length 25.0 mm ± 2.0 mm		BFC2 338 14 ...
Taped on reel <sup>(1)</sup>	Bent back to 7.5 mm; H = 16.0 mm; P <sub>0</sub> = 15.0 mm; reel diameter = 500 mm	BFC2 338 16 ...		
	ALTERNATIVE TAPED VERSIONS			ON REQUEST
	338 1 X1 X1	Taped on reel <sup>(1)</sup>		H = 18.5 mm; for P <sub>0</sub> = 12.7 mm; reel diameter = 500 mm
		ALTERNATIVE C-TOL.	ON REQUEST	
338 1 X1	Loose in box	Lead length 3.5 mm ± 0.3 mm	± 10 %	See tables for detail
			± 5 %	
		Lead length 5.0 mm ± 1.0 mm	± 10 %	
		± 5 %		
	Lead length 25.0 mm ± 2.0 mm	± 10 %		
		± 5 %		
Taped on reel <sup>(1)</sup>	Bent back to 7.5 mm; H = 16.0 mm; P <sub>0</sub> = 15.0 mm; reel diameter = 500 mm	± 10 %		
		± 5 %		
	H = 18.5 mm; P <sub>0</sub> = 12.7 mm; reel diameter = 500 mm	± 10 %		
		± 5 %		

### Note

<sup>(1)</sup> For detailed tape specification refer to Packaging Information: [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139)

## SPECIFIC REFERENCE DATA

DESCRIPTION	VALUE	
Rated AC voltage (U <sub>RAC</sub> )	440 V	
Permissible DC voltage (U <sub>RDC</sub> )	1000 V	
Tangent of loss angle:	at 1 kHz	at 10 kHz
C ≤ 470 nF	≤ 10 x 10 <sup>-4</sup>	≤ 20 x 10 <sup>-4</sup>
C > 470 nF	≤ 20 x 10 <sup>-4</sup>	≤ 70 x 10 <sup>-4</sup>
Rated voltage pulse slope (dU/dt) <sub>R</sub> at 615 V <sub>DC</sub>		
Pitch = 15 mm and 7.5 mm (bent back)	250 V/μs	
Pitch = 22.5 mm	150 V/μs	
Pitch = 27.5 mm	100 V/μs	
R between leads, for C ≤ 0.33 μF at 100 V, 1 min	> 15 000 MΩ	
RC between leads, for C > 0.33 μF at 100 V, 1 min	> 5000 s	
R between leads and case, 100 V, 1 min	> 30 000 MΩ	
Withstanding (DC) voltage (cut off current 10 mA), rise time ≤ 1000 V/s	3400 V, 1 min	
Withstanding (AC) voltage between leads and case	2380 V, 1 min	
Maximum application temperature	105 °C	

### Note

<sup>(1)</sup> See "Voltage Proof Test for Metallized Film Capacitors": [www.vishay.com/doc?28169](http://www.vishay.com/doc?28169)



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

C-tol. = ± 20 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER BFC2 338 1XXXX AND PACKAGING						
			LOOSE IN BOX				TAPED		
			Short leads		Long leads		Reel diameter = 500 mm <sup>(1)(2)</sup>		
			$l_t = 3.5 \text{ mm} \pm 0.3 \text{ mm}$	$l_t = 5.0 \text{ mm} \pm 1.0 \text{ mm}$	SPQ	$l_t = 25.0 \text{ mm} \pm 2.0 \text{ mm}$	SPQ	H = 18.5 mm; P <sub>0</sub> = 12.7 mm	SPQ
<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.60 mm ± 0.06 mm</b>									
0.01	5.0 x 11.0 x 17.5	1.0	10103	12103	1000	14103	1000	17103	1100
0.012			10123	12123		14123		17123	
0.015			10153	12153		14153		17153	
0.018			10183	12183		14183		17183	
0.022			10223	12223		14223		17223	
0.027	6.0 x 12.0 x 17.5	1.4	10273	12273	1000	14273	1000	17273	900
0.033			10333	12333		14333		17333	
<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.039	7.0 x 13.5 x 17.5	1.8	10393	12393	750	14393	500	17393	800
0.047			10473	12473		14473		17473	
0.056	8.5 x 15.0 x 17.5	2.4	10563	12563	750	14563	500	17563	650
0.068			10683	12683		14683		17683	
0.082	10.0 x 16.5 x 17.5	3.0	10823	12823	500	14823	450	17823	600
0.1			10104	12104		14104		17104	
<b>Pitch = 22.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.12	8.5 x 18.0 x 26.0	3.8	10124	12124	200	14124	250	17124	450
0.15			10154	12154		14154		17154	
0.18	10.0 x 19.5 x 26.0	6.8	10184	12184	200	14184	200	17184	350
0.22			10224	12224		14224		17224	
<b>Pitch = 27.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.27	11.0 x 21.0 x 31.0	7.4	10274	12274	100	14274	125		
0.33	13.0 x 23.0 x 31.0	9.2	10334	12334	100	14334	125		
0.39	15.0 x 25.0 x 31.5	12.3	10394	12394	100	14394	125		
0.47			10474	12474		14474			
0.56	18.0 x 28.0 x 31.5	16.1	10564	12564	100	14564	100		
0.68			10684	12684		14684			
0.82	21.0 x 31.0 x 31.0	20.3	10824	12824	50	14824	75		
1.00			10105	12105		14105			

**Notes**

- SPQ = Standard Packing Quantity

<sup>(1)</sup> H = in-tape height; P<sub>0</sub> = sprocket hole distance; for detailed specifications refer to “Packaging Information”

<sup>(2)</sup> Reel diameter = 356 mm is available on request

<sup>(3)</sup> Weight for short lead product only

Bent back pitch 7.5 mm (only taped); C-tol. = ± 20 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER BFC2 338 1XXXX AND PACKAGING						
			LOOSE IN BOX					TAPED	
			Short leads			Long leads		Reel diameter = 500 mm <sup>(1)(2)</sup>	
			$l_t =$ 3.5 mm ± 0.3 mm	$l_t =$ 5.0 mm ± 1.0 mm	SPQ	$l_t =$ 25.0 mm ± 2.0 mm	SPQ	H = 16.0 mm; P <sub>0</sub> = 15.0 mm	SPQ
<b>Original pitch = 15.0 mm; bent back pitch = 7.5 mm ± 0.4 mm; d<sub>t</sub> = 0.60 mm ± 0.06 mm</b>									
0.010 0.012 0.015 0.018 0.022	5.0 x 13.0 x 17.5	1.0						16103 16123 16153 16183 16223	950
0.027 0.033	6.0 x 14.0 x 17.5	1.4						16273 16333	800
<b>Original pitch = 15.0 mm; bent back pitch = 7.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.039 0.047	7.0 x 15.5 x 17.5	1.8						16393 16473	700
0.056 0.068	8.5 x 17.0 x 17.5	1.4						16563 16683	550
0.082 0.100	10.0 x 18.5 x 17.5	3.0						16823 16104	500

### Notes

- SPQ = Standard Packing Quantity

<sup>(1)</sup> H = in-tape height; P<sub>0</sub> = sprocket hole distance; for detailed specifications refer to "Packaging Information"

<sup>(2)</sup> Reel diameter = 356 mm is available on request

<sup>(3)</sup> Weight for short lead product only

C-tol. = ± 10 %

C (μF)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER BFC2 338 1XXXX AND PACKAGING						
			LOOSE IN BOX					TAPED	
			Short leads			Long leads		Reel diameter = 500 mm <sup>(1)(2)</sup>	
			$l_t =$ 3.5 mm ± 0.3 mm	$l_t =$ 5.0 mm ± 1.0 mm	SPQ	$l_t =$ 25.0 mm ± 2.0 mm	SPQ	H = 18.5 mm; P <sub>0</sub> = 12.7 mm	SPQ
<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.60 mm ± 0.06 mm</b>									
0.010 0.012 0.015 0.018	5.0 x 11.0 x 17.5	1.0	18114 18115 18116 18117	18314 18315 18316 18317	1000	18514 18515 18516 18517	1000	18914 18915 18916 18917	1100
0.022 0.027	6.0 x 12.0 x 17.5	1.4	18118 18119	18318 18319	1000	18518 18519	1000	18918 18919	900
<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.033 0.039	7.0 x 13.5 x 17.5	1.8	18121 18122	18321 18322	750	18521 18522	500	18921 18922	800
0.047 0.056	8.5 x 15.0 x 17.5	2.4	18123 18124	18323 18324	750	18523 18524	500	18923 18924	650
0.068 0.082	10.0 x 16.5 x 17.5	3.0	18125 18126	18325 18326	500	18525 18526	450	18925 18926	600



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

C ( $\mu$ F)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER BFC2 338 1XXXX AND PACKAGING						
			LOOSE IN BOX					TAPED	
			Short leads			Long leads		Reel diameter = 500 mm <sup>(1)(2)</sup>	
			$l_t =$ 3.5 mm $\pm$ 0.3 mm	$l_t =$ 5.0 mm $\pm$ 1.0 mm	SPQ	$l_t =$ 25.0 mm $\pm$ 2.0 mm	SPQ	H = 18.5 mm; P <sub>0</sub> = 12.7 mm	SPQ
<b>Pitch = 22.5 mm <math>\pm</math> 0.4 mm; d<sub>t</sub> = 0.80 mm <math>\pm</math> 0.08 mm</b>									
0.10	7.0 x 16.5 x 26.0	2.9	18127	18327	200	18527	250	18927	550
0.12	8.5 x 18.0 x 26.0	3.8	18128	18328	200	18528	250	18928	450
0.15			18129	18329		18529		18929	
0.18	10.0 x 19.5 x 26.0	6.8	18131	18331	200	18531	200	18931	350
<b>Pitch = 27.5 mm <math>\pm</math> 0.4 mm; d<sub>t</sub> = 0.80 mm <math>\pm</math> 0.08 mm</b>									
0.22	11.0 x 21.0 x 31.0	7.4	18132	18332	100	18532	125		
0.27			18133	18333		18533			
0.33	13.0 x 23.0 x 31.0	9.2	18134	18334	100	18534	125		
0.39	15.0 x 25.0 x 31.0	12.3	18135	18335	100	18535	125		
0.47			18136	18336		18536			
0.56	18.0 x 28.0 x 31.0	16.1	18137	18337	100	18537	100		
0.68			18138	18338		18538			
0.82	21.0 x 31.0 x 31.0	20.3	18139	18339	50	18539	75		

Notes

- SPQ = Standard Packing Quantity
- (1) H = in-tape height; P<sub>0</sub> = sprocket hole distance; for detailed specifications refer to “Packaging Information”
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

**Bent back pitch 7.5 mm (only taped); C-tol. =  $\pm$  10 %**

C ( $\mu$ F)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER BFC2 338 1XXXX AND PACKAGING						
			LOOSE IN BOX					TAPED	
			Short leads			Long leads		Reel diameter = 500 mm <sup>(1)(2)</sup>	
			$l_t =$ 3.5 mm $\pm$ 0.3 mm	$l_t =$ 5.0 mm $\pm$ 1.0 mm	SPQ	$l_t =$ 25.0 mm $\pm$ 2.0 mm	SPQ	H = 18.5 mm; P <sub>0</sub> = 12.7 mm	SPQ
<b>Original pitch = 15.0 mm; bent back pitch = 7.5 mm <math>\pm</math> 0.4 mm; d<sub>t</sub> = 0.60 mm <math>\pm</math> 0.06 mm</b>									
0.010	5.0 x 13.0 x 17.5	1.0						18714	950
0.012								18715	
0.015								18716	
0.018								18717	
0.022	6.0 x 14.0 x 17.5	1.4						18718	800
0.027								18719	
<b>Original pitch = 15.0 mm; bent back pitch = 7.5 mm <math>\pm</math> 0.4 mm; d<sub>t</sub> = 0.80 mm <math>\pm</math> 0.08 mm</b>									
0.033	7.0 x 15.5 x 17.5	1.8						18721	700
0.039								18722	
0.047	8.5 x 17.0 x 17.5	2.4						18723	550
0.056								18724	
0.068	10.0 x 18.5 x 17.5	3.0						18725	500
0.082								18726	

Notes

- SPQ = Standard Packing Quantity
- (1) H = in-tape height; P<sub>0</sub> = sprocket hole distance; for detailed specifications refer to “Packaging Information”
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

# MKP338 1 X1



## Vishay BCcomponents Interference Suppression Film Capacitors MKP Radial Potted Type

C-tol. = ± 5 %

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER BFC2 338 1XXXX AND PACKAGING						
			LOOSE IN BOX				TAPED		
			Short leads		Long leads		Reel diameter = 500 mm <sup>(1)(2)</sup>		
			$l_t =$ 3.5 mm ± 0.3 mm	$l_t =$ 5.0 mm ± 1.0 mm	SPQ	$l_t =$ 25.0 mm ± 2.0 mm	SPQ	H = 18.5 mm; P <sub>0</sub> = 12.7 mm	SPQ
<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.60 mm ± 0.06 mm</b>									
0.010	5.0 x 11.0 x 17.5	1.0	18214	18414	1000	18614	1000	18934	1100
0.012			18215	18415		18615		18935	
0.015			18216	18416		18616		18936	
0.018			18217	18417		18617		18937	
0.022			18218	18418		18618		18938	
0.027	6.0 x 12.0 x 17.5	1.4	18219	18419	1000	18619	1000	18939	900
<b>Pitch = 15.0 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.033	7.0 x 13.5 x 17.5	1.8	18221	18421	750	18621	500	18941	800
0.039			18222	18422		18622		18942	
0.047	8.5 x 15.0 x 17.5	2.4	18223	18423	750	18623	500	18943	650
0.056			18224	18424		18624		18944	
0.068	10.0 x 16.5 x 17.5	3.0	18225	18425	500	18625	450	18945	600
0.082			18226	18426		18626		18946	
<b>Pitch = 22.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.10	8.5 x 18.0 x 26.0	3.8	18227	18427	200	18627	250	18947	450
0.12			18228	18428		18628		18948	
0.15	10.0 x 19.5 x 26.0	6.8	18229	18429	200	18629	200	18949	350
0.18			18231	18431		18631		18951	
<b>Pitch = 27.5 mm ± 0.4 mm; d<sub>t</sub> = 0.80 mm ± 0.08 mm</b>									
0.22	11.0 x 21.0 x 31.0	7.4	18232	18432	100	18632	125		
0.27	13.0 x 23.0 x 31.0	9.2	18233	18433	100	18633	125		
0.33			18234	18434		18634			
0.39	15.0 x 25.0 x 31.5	12.3	18235	18435	100	18635	125		
0.47			18236	18436		18636			
0.56	18.0 x 28.0 x 31.5	16.1	18237	18437	100	18637	100		
0.68			18238	18438		18638			
0.82	21.0 x 31.0 x 31.0	20.3	18239	18439	50	18639	75		

### Notes

- SPQ = Standard Packing Quantity
- (1) H = in-tape height; P<sub>0</sub> = sprocket hole distance; for detailed specifications refer to "Packaging Information"
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

**Bent back pitch (only taped); C-tol. = ± 5 %**

C (µF)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER BFC2 338 1XXXX AND PACKAGING						
			LOOSE IN BOX				TAPED		
			Short leads		Long leads		Reel diameter = 500 mm <sup>(1)</sup>		
			$l_t =$ 3.5 mm ± 0.3 mm	$l_t =$ 5.0 mm ± 1.0 mm	SPQ	$l_t =$ 25.0 mm ± 2.0 mm	SPQ	H = 16.0 mm; P <sub>0</sub> = 15.0 mm	SPQ
<b>Original pitch = 15.0 mm; bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>									
0.010	5.0 x 13.0 x 17.5	1.0					18814	950	
0.012							18815		
0.015							18816		
0.018							18817		
0.022							18818		
0.027	6.0 x 14.0 x 17.5	1.4					18819	800	
<b>Original pitch = 15.0 mm; bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.80 ± 0.08 mm</b>									
0.033	7.0 x 15.5 x 17.5	1.8					18821	700	
0.039							18822		
0.047	8.5 x 17.0 x 17.5	2.4					18823	550	
0.056							18824		
0.068	10.0 x 18.5 x 17.5	3.0					18825	500	
0.082							18826		

### Notes

- SPQ = Standard Packing Quantity
- (1) H = in-tape height; P<sub>0</sub> = sprocket hole distance; for detailed specifications refer to "Packaging Information"
- (2) Reel diameter = 356 mm is available on request
- (3) Weight for short lead product only

**APPROVALS**

SAFETY APPROVALS X1	VOLTAGE	VALUE	FILE NUMBERS
EN 60384-14 (ENEC) (= IEC 60384-14 ed-3)	440 V <sub>AC</sub>	10 nF to 1 μF	FI 2008060 A1
UL1414	250 V <sub>AC</sub>	10 nF to 1 μF	E112471
UL1283	440 V <sub>AC</sub>	10 nF to 100 nF	E109565
UL1283 and (CSA-C22.2 No. 8)	440 V <sub>AC</sub>	100 nF to 1 μF	E109565
CB-Test Certificate	440 V <sub>AC</sub>	10 nF to 1 μF	FI 5256 A1

The ENEC-approval together with the CB-Certificate replace all national marks of the following countries (they have already signed the ENEC-Agreement): Austria; Belgium; Czech. Republic; Denmark; Finland; France; Germany; Greece; Hungary; Ireland; Italy; Luxembourg; Netherlands; Norway; Portugal; Slovenian; Spain; Switzerland and United Kingdom.

**MOUNTING**
**Normal Use**

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoliers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to: "Packaging Information": [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139)

**Specific Method of Mounting to Withstand Vibration and Shock**

In order to withstand vibration and shock tests, it must be ensured that the stand-off pips are in good contact with the printed-circuit board:


- For pitches  $\leq 15$  mm capacitors shall be mechanically fixed by the leads
- For longer pitches the capacitors shall be mounted in the same way and the body clamped

**Space Requirements on Printed Circuit Board**

The maximum space for length ( $l_{max.}$ ), width ( $w_{max.}$ ) and height ( $h_{max.}$ ) of film capacitors to take in account on the printed circuit board is shown in the drawings.

- For products with pitch  $\leq 15$  mm,  $\Delta w = \Delta l = 0.3$  mm;  $\Delta h = 0.1$  mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.


**SOLDERING**

For general soldering conditions and wave soldering profile, we refer to the application note:

"Soldering Guidelines for Film Capacitors": [www.vishay.com/doc?28171](http://www.vishay.com/doc?28171)

**Storage Temperature**

- Storage temperature:  $T_{stg} = -25$  °C to  $+40$  °C with RH maximum 80 % without condensation

**Ratings and Characteristics Reference Conditions**


Unless otherwise specified, all electrical values apply to an ambient temperature of  $23$  °C  $\pm 1$  °C, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50$  %  $\pm 2$  %.

For reference testing, a conditioning period shall be applied over  $96$  h  $\pm 4$  h by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.




## CHARACTERISTICS


Capacitance as a function of ambient temperature (typical curve)




Tangent of loss angle as a function of frequency (typical curve)




Impedance as a function of frequency (typical curve)




Resonant frequency as a function of capacitance (typical curve)



Max. RMS voltage as a function of frequency




Max. RMS current as a function of frequency



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

Insulation resistance as a function of ambient temperature



### APPLICATION NOTES

- For X1 electromagnetics interference suppression in **standard across the line applications** (50 Hz/60 Hz) with a maximum mains voltage of 440 V<sub>AC</sub>.
- For series impedance applications we refer to Application Note [www.vishay.com/doc?28153](http://www.vishay.com/doc?28153)
- For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: [dc-film@vishay.com](mailto:dc-film@vishay.com)
- These capacitors are not intended for continuous pulse applications. For these situations, capacitors of the AC and pulse programs must be used.
- The maximum ambient temperature must not exceed 105 °C.
- Rated voltage pulse slope:  
If the pulse voltage is lower than the rated voltage, the values of the specific reference data can be multiplied by 615 V<sub>DC</sub> and divided by the applied voltage.



## INSPECTION REQUIREMENTS

### General Notes:

- Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-14 ed-3 and Specific Reference Data.”


### Group C Inspection Requirements

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b>		
4.1 Dimensions (detail)		As specified in chapters “General data” of this specification
Initial measurements	Capacitance Tangent of loss angle at 10 kHz	
4.3 Robustness of terminations	Tensile: load 10 N; 10 s Bending: load 5 N; 4 x 90°	No visible damage
4.4 Resistance to soldering heat	No pre-drying Method: 1A Solder bath: 280 °C ± 5 °C Duration: 10 s	
4.19 Component solvent resistance	Isopropylalcohol at room temperature Method: 2 Immersion time: 5 min ± 0.5 min Recovery time: Min. 1 h, max. 2 h	
4.4.2 Final measurements	Visual examination	No visible damage Legible marking
	Capacitance	$ \Delta C/C  \leq 5\%$ of the value measured initially
	Tangent of loss angle	Increase of $\tan \delta \leq 0.008$ Compared to values measured initially
	Insulation resistance	As specified in section “Insulation Resistance” of this specification
<b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b>		
Initial measurements	Capacitance Tangent of loss angle at 10 kHz	
4.20 Solvent resistance of the marking	Isopropylalcohol at room temperature Method: 1 Rubbing material: cotton wool Immersion time: 5 min ± 0.5 min	No visible damage Legible marking
4.6 Rapid change of temperature	θA = - 55 °C θB = + 105 °C 5 cycles  Duration t = 30 min	



SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C2</b>		
4.12 Damp heat steady state	56 days, 40 °C, 90 % to 95 % RH No load	
4.12.1 Initial measurements  4.12.3 Final measurements	Capacitance Tangent of loss angle at 1 kHz  Visual examination  Capacitance  Tangent of loss angle  Voltage proof 1900 V <sub>DC</sub> ; 1 min between terminations  Insulation resistance	No visible damage Legible marking  $ \Delta C/C  \leq 5\%$ of the value measured in 4.12.1.  Increase of $\tan \delta \leq 0.008$ Compared to values measured in 4.12.1.  No permanent breakdown or flash-over  $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification
<b>SUB-GROUP C3</b>		
4.13.1 Initial measurements  4.13 Impulse voltage  4.14 Endurance  4.14.7 Final measurements	Capacitance Tangent of loss angle at 10 kHz  3 successive impulses, full wave, peak voltage: X1: 4 kV Max. 24 pulses  Duration: 1000 h 1.25 x U <sub>RAC</sub> at 105 °C Once in every hour the voltage is increased to 1000 V <sub>RMS</sub> for 0.1 s via resistor of 47 Ω ± 5 %  Visual examination  Capacitance  Tangent of loss angle  Voltage proof 1900 V <sub>DC</sub> ; 1 min between terminations 2380 V <sub>AC</sub> ; 1 min between terminations and case.  Insulation resistance	No self healing breakdowns or flash-over      No visible damage Legible marking  $ \Delta C/C  \leq 10\%$ compared to values measured in 4.13.1.  Increase of $\tan \delta \leq 0.008$ Compared to values measured in 4.13.1.  No permanent breakdown or flash-over  $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification
<b>SUB-GROUP C4</b>		
4.15 Charge and discharge  4.15.1 Initial measurements	10 000 cycles  Charged to 615 V <sub>DC</sub> Discharge resistance: $R = \frac{615 V_{DC}}{1.5 \times C (dU/dt)}$  Capacitance Tangent of loss angle at 10 kHz	

Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
4.15.3 Final measurements	Capacitance  Tangent of loss angle  Insulation resistance	$ \Delta C/C  \leq 10\%$ compared to values measured in 4.15.1.  Increase of $\tan \delta \leq 0.008$ Compared to values measured in 4.15.1.  $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification
<b>SUB-GROUP C5</b>		
4.16 Radio frequency characteristic	Resonance frequency	$\geq 0.9$ times value as specified in section "Resonant Frequency" of this specification
<b>SUB-GROUP C6</b>		
4.17 Passive flammability Class B	Bore of gas jet: $\varnothing 0.5$ mm Fuel: Butane Test duration for actual volume $V$ in $\text{mm}^3$ : $V \leq 250$ : 10 s $250 < V \leq 500$ : 20 s $500 < V \leq 1750$ : 30 s $V > 1750$ : 60 s One flame application  	After removing test flame from capacitor, the capacitor must not continue to burn for more than 10 s. No burning particle must drop from the sample.
<b>SUB-GROUP C7</b>		
4.18 Active flammability	20 cycles of 4 kV discharges on the test capacitor connected to $U_{RAC}$	The cheese cloth around the capacitors shall not burn with a flame. No electrical measurements are required.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**