



BURNDY Catalog Number
UPC Number
Description
Status

BISR1DB
 7818102880477
 2-1 DIRECTBURIAL UNITAP
 Active

Web Use
 BURNDY Product Line

Dimensional	
Screw Size	5/16
Width (in)	0.88
Hex Size (Key)	5/32
Length (in)	6.30
Height (in)	1.75
Electrical	
Min Voltage Rating	600
General	
Number of Ports	2
Number of Screws	2
Product Description	In-Line Splice/Reducer, 2 Port, 2-1 AWG, Al/Cu Rated
Conductor(s)	
Aluminum Size (Range)	2 AWG-1 AWG
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	#2 AWG-#1 AWG
Physical	
Type of Hardware	Aluminum
Installation Torque	130
Type of Plating	Unplated
Insulation Type	Plastisol
Plated (Yes or No)	N
Product Material	Aluminum
Approvals / Certifications	
UL Listed	Y
CSA Certified	N
Rated for Direct Burial	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175