



BURNDY Catalog Number
UPC Number
Description
Status

BISR4DB
 7818102880544
 4-6 DIRECTBURIAL UNITAP
 Active

Web Use
 BURNDY Product Line

Screw Size 1/4
 Width (in) 0.68
 Hex Size (Key) 1/8
 Length (in) 4.30
 Height (in) 1.39

Dimensional

Electrical
 600

Min Voltage Rating

General

Number of Ports 2
 Number of Screws 2

In-Line Splice/Reducer, 2 Port, 6-4
 AWG, Al/Cu Rated

Product Description

Conductor(s)

Aluminum Size (Range)
 Copper Solid Size (Range)
 Copper Stranded (Range)

6 AWG-4 AWG
 N/A
 #6 AWG-#4 AWG

Physical

Insulation Type
 Type of Hardware
 Installation Torque
 Type of Plating
 Plated (Yes or No)
 Product Material

Plastisol
 Aluminum
 50
 Unplated
 N
 Aluminum

Approvals / Certifications

UL Listed
 Rated for Direct Burial
 ROHS Compatible
 Industry Standards

Y
 Y
 Compliant
 UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175