


# Surface Mount Glass Passivated Junction Fast Switching Rectifier

**SUPERECTIFIER®**

**DO-213AB**

PRIMARY CHARACTERISTICS	
$I_{F(AV)}$	1.0 A
$V_{RRM}$	50 V to 1000 V
$I_{FSM}$	30 A
$t_{rr}$	150 ns, 250 ns, 500 ns
$V_F$	1.3 V
$T_J \text{ max.}$	175 °C
Package	DO-213AB (GL41)
Diode variation	Single die

**TYPICAL APPLICATIONS**

For use in fast switching rectification of power supply, inverters, converters, and freewheeling diodes for consumer, automotive and telecommunication.

**FEATURES**

- Superectifier structure for high reliability condition
- Ideal for automated placement
- Fast switching for high efficiency
- Low leakage current
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 250 °C
- AEC-Q101 qualified
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

**MECHANICAL DATA**

**Case:** DO-213AB, molded epoxy over glass body  
Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS-compliant, commercial grade  
Base P/NHE3 - RoHS-compliant, AEC-Q101 qualified

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

**Polarity:** Two bands indicate cathode end - 1<sup>st</sup> band denotes device type and 2<sup>nd</sup> band denotes repetitive peak reverse voltage rating

MAXIMUM RATINGS ( $T_A = 25\text{ °C}$ unless otherwise noted)									
PARAMETER	SYMBOL	BYM 11-50	BYM 11-100	BYM 11-200	BYM 11-400	BYM 11-600	BYM 11-800	BYM 11-1000	UNIT
		RGL41A	RGL41B	RGL41D	RGL41G	RGL41J	RGL41K	RGL41M	
<b>FAST SWITCHING TIME DEVICE: 1<sup>ST</sup> BAND IS RED</b>									
Polarity color bands (2 <sup>nd</sup> band)		Gray	Red	Orange	Yellow	Green	Blue	Violet	
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum average forward rectified current at $T_T = 55\text{ °C}$	$I_{F(AV)}$	1.0							A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	$I_{FSM}$	30							A
Maximum full load reverse current, full cycle average at $T_A = 55\text{ °C}$	$I_{R(AV)}$	50							$\mu\text{A}$
Operating junction and storage temperature range	$T_J, T_{STG}$	- 65 to + 175							°C



**ELECTRICAL CHARACTERISTICS** ( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)

PARAMETER	TEST CONDITIONS	SYMBOL	BYM 11-50	BYM 11-100	BYM 11-200	BYM 11-400	BYM 11-600	BYM 11-800	BYM 11-1000	UNIT
Maximum instantaneous forward voltage	1.0 A	$V_F$	1.3							V
Maximum DC reverse current at rated DC blocking voltage	$T_A = 25\text{ }^\circ\text{C}$	$I_R$	5.0							$\mu\text{A}$
	$T_A = 125\text{ }^\circ\text{C}$		50							
Maximum reverse recovery time	$I_F = 0.5\text{ A}$ , $I_R = 1.0\text{ A}$ , $I_{rr} = 0.25\text{ A}$	$t_{rr}$	150				250	500		ns
Typical junction capacitance	4.0 V, 1 MHz	$C_J$	15							pF

**THERMAL CHARACTERISTICS** ( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)

PARAMETER	SYMBOL	BYM 11-50	BYM 11-100	BYM 11-200	BYM 11-400	BYM 11-600	BYM 11-800	BYM 11-1000	UNIT
Maximum thermal resistance	$R_{\theta JA}^{(1)}$	75							$^\circ\text{C/W}$
	$R_{\theta JT}^{(2)}$	30							

**Notes**

- (1) Thermal resistance from junction to ambient, 0.24" x 0.24" (6.0 mm x 6.0 mm) copper pads to each terminal
- (2) Thermal resistance from junction to terminal, 0.24" x 0.24" (6.0 mm x 6.0 mm) copper pads to each terminal

**ORDERING INFORMATION** (Example)

PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
RGL41J-E3/96	0.114	96	1500	7" diameter plastic tape and reel
RGL41J-E3/97	0.114	97	5000	13" diameter plastic tape and reel
BYM11-600-E3/96	0.114	96	1500	7" diameter plastic tape and reel
BYM11-600-E3/97	0.114	97	5000	13" diameter plastic tape and reel
RGL41JHE3/96 <sup>(1)</sup>	0.114	96	1500	7" diameter plastic tape and reel
RGL41JHE3/97 <sup>(1)</sup>	0.114	97	5000	13" diameter plastic tape and reel
BYM11-600HE3/96 <sup>(1)</sup>	0.114	96	1500	7" diameter plastic tape and reel
BYM11-600HE3/97 <sup>(1)</sup>	0.114	97	5000	13" diameter plastic tape and reel

**Note**

- (1) AEC-Q101 qualified

**RATINGS AND CHARACTERISTICS CURVES** ( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 4 - Typical Reverse Characteristics






Fig. 6 - Typical Transient Thermal Impedance

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)



1<sup>st</sup> band denotes type and positive end (cathode)

**Mounting Pad Layout**





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Vishay:

[RGL41A/51](#) [RGL41A/96](#) [RGL41A-E3/51](#) [RGL41A-E3/96](#) [RGL41AHE3/96](#) [RGL41B/25](#) [RGL41B/26](#) [RGL41B/46](#)  
[RGL41B/51](#) [RGL41B/75](#) [RGL41B/96](#) [RGL41B-E3/51](#) [RGL41B-E3/75](#) [RGL41B-E3/76](#) [RGL41B-E3/96](#)  
[RGL41BHE3/75](#) [RGL41BHE3/76](#) [RGL41BHE3/96](#) [RGL41D/25](#) [RGL41D/46](#) [RGL41D/51](#) [RGL41D/75](#) [RGL41D/76](#)  
[RGL41D/96](#) [RGL41D-E3/51](#) [RGL41D-E3/75](#) [RGL41D-E3/76](#) [RGL41D-E3/96](#) [RGL41DHE3/75](#) [RGL41DHE3/76](#)  
[RGL41DHE3/96](#) [RGL41G/25](#) [RGL41G/46](#) [RGL41G/51](#) [RGL41G/75](#) [RGL41G/76](#) [RGL41G/96](#) [RGL41G-E3/51](#)  
[RGL41G-E3/75](#) [RGL41G-E3/76](#) [RGL41G-E3/96](#) [RGL41GHE3/75](#) [RGL41GHE3/76](#) [RGL41GHE3/96](#) [RGL41J/25](#)  
[RGL41J/26](#) [RGL41J/46](#) [RGL41J/51](#) [RGL41J/75](#) [RGL41J/76](#) [RGL41J/96](#) [RGL41J-E3/51](#) [RGL41J-E3/75](#) [RGL41J-](#)  
[E3/76](#) [RGL41J-E3/96](#) [RGL41JHE3/75](#) [RGL41JHE3/76](#) [RGL41JHE3/96](#) [RGL41K/25](#) [RGL41K/26](#) [RGL41K/46](#)  
[RGL41K/51](#) [RGL41K/75](#) [RGL41K/76](#) [RGL41K/96](#) [RGL41K-E3/51](#) [RGL41K-E3/75](#) [RGL41K-E3/76](#) [RGL41K-E3/96](#)  
[RGL41KHE3/75](#) [RGL41KHE3/76](#) [RGL41KHE3/96](#) [RGL41M/26](#) [RGL41M/46](#) [RGL41M/51](#) [RGL41M/76](#) [RGL41M/96](#)  
[RGL41M-E3/51](#) [RGL41M-E3/76](#) [RGL41M-E3/96](#) [RGL41MHE3/76](#) [RGL41MHE3/96](#) [BYM11-1000-E3/76](#) [BYM11-](#)  
[1000-E3/96](#) [BYM11-1000HE3/76](#) [BYM11-1000HE3/96](#) [BYM11-100-E3/76](#) [BYM11-100-E3/96](#) [BYM11-100HE3/76](#)  
[BYM11-100HE3/96](#) [BYM11-200-E3/26](#) [BYM11-200-E3/75](#) [BYM11-200-E3/76](#) [BYM11-200-E3/96](#) [BYM11-200HE3/75](#)  
[BYM11-200HE3/76](#) [BYM11-200HE3/96](#) [BYM11-400-E3/26](#) [BYM11-400-E3/76](#) [BYM11-400-E3/96](#)