

## Eaton Type MTE industrial control transformer

**C0250EBHFBFS**

**UPC:**786680057366

### **Dimensions:**

- **Height:** 7.25 IN
- **Length:** 5 IN
- **Width:** 5 IN

**Weight:**9.314 LB

**Notes:**Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** Factory-mounted 2-pole primary fuse block for rejection type fuses
- **Modification 2:** Factory-mounted finger-safe terminal shields
- **Primary Voltage:** 277V
- **Secondary Voltage:** 120V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** Industrial Control Transformer
- **Volt Ampere Rating:** 250 VA

### **Supporting documents:**

- [dry-type distribution transformer-flex center line card](#)

- [Industrial control transformers brochure](#)
- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Transformer distribution catalog, volume 2, tab 2](#)
- [Eaton Specification Sheet - C0250EBHFBFS](#)
- [Transformer consulting application guide](#)

**Certifications:**

- UL Listed
- CSA Certified
- cUL Certified

**Product compliance:**

- RoHS Compliant